



W.J. KEATING LIMITED

Blocks for Manila Rope

These blocks are furnished with grooved bronze bushings which are pressure grease lubricated. Galvanized finish. Shells and fittings are drop forged.



Single
K-1401



Double
K-1402



Triple
K-1403

Specifications

Block Size, Inches		8	10	12
Diameter Rope, Inches		1	1 1/4	1 1/2
Sheave Size, Inches	O.D.	4 3/4	6 1/4	8
	Rim	1 1/8	1 1/2	1 5/8
	Ctr. Pin Dia.	3/4	3/4	7/8
Weight in Pounds	Single	17	25	34
	Double	24	39	56
	Triple	32	48	72
Working Load Limit*, Tons	Single	2	3	4
	Double	3	5	7
	Triple	4	6	8

Stock Numbers

Bronze Bushed Galv	Single	925-5845	925-6045	925-6245
	Double	925-7345	925-7545	925-7745
	Triple	925-8945	925-9145	925-9345

Gin or Roofers' Block for Manila Rope

This block is furnished with a drop forged, flatted, swivel hook with latch. Roller bushing. Painted finish.



K-405

Star Safety Tackle Blocks for Manila Rope

These blocks feature drop forged fittings, self-lubricating bushings and a painted finish. They grip the load when the hoist strain is removed. Must be used for vertical lifting only. Rope is not included.

Block Size, Inches	Stock Number	Rope Dia., Inches
2	928-9802	3/8-1/2
4	928-9804	5/8-3/4

Weight in Pounds	Working Load Limit*, Pounds	Pounds One Man Can Lift
8	1,000	400
25	2,800	600



K-407

Block Size, Inches	Rope Dia., Inches	Sheave Size, Inches			Block Weight, Pounds	Working Load Limit*, Pounds	Stock Number	
		Outside Dia.	Rim	Center Pin Dia.			Block	Replacement Sheave
12	1	12	1 3/8	5/8	15.5	1,000	926-9812	934-3922

Working Load is resultant Working Load. Lift should not exceed 500 pounds.