



HEADACHE BALL ASSEMBLIES




(SHOWN ABOVE IS A TYPE 2 HEADACHE BALL)

- 4 types — clevis, eye wedge, or thimble caps.
- Working loads from 5 to 35 tons.
- Overhaul weights from 65 to 750 lbs.
- For wire rope sizes from 1/2" to 1 1/2".

K-1079 Headache Ball Assembly with wedge cap.

When ordering Type 3 specify wire rope size

Part No.	Wire Rope Size	a	b	c	d	e	f	g	Wgt.	Max. Load Tons
060-5624	1/2, 3/4	18 1/4	7	25 1/8	1 3/8	1 1/8	1 1/8	1 3/4	65	5
060-5642	1/2, 3/4	18 1/4	8.5	25 1/8	1 3/8	1 1/8	1 1/8	1 3/4	100	5
060-5660	3/4, 1, 1 1/4	21 1/4	9	30 1/2	2 1/2	2 1/4	2 1/4	2 3/4	130	8.5
060-5704	3/4, 1, 1 1/4	21 1/4	10	30 1/2	2 1/2	2 1/4	2 1/4	2 3/4	170	8.5
060-7409	3/4, 1, 1 1/4	22 1/8	11	31 3/8	2 1/2	2 1/4	2 1/4	2 3/4	215	8.5
060-7427	3/4, 1, 1 1/4	22 1/8	12	31 3/8	2 1/2	2 1/4	2 1/4	2 3/4	265	8.5
060-7445	3/4, 1, 1 1/4	23 1/8	13	32 3/8	2 1/2	2 1/4	2 1/4	2 3/4	336	8.5
060-7463	3/4, 1, 1 1/4	27 3/8	13	38 3/8	3 3/8	3	3	3 3/8	370	10
060-7506	3/4, 1, 1 1/4	27 3/8	13	38 3/8	3 3/8	3	3	3 3/8	370	15
060-7524	1 1/4, 1 1/2	34 3/8	13	46 3/8	4	3 1/2	3 1/2	3 3/4	439	25
060-7542	1 1/4, 1 1/2	34 3/8	13	50 3/8	4 1/4	3 3/4	4 3/4	4 1/2	513	35
060-8006	3/4, 1, 1 1/4	28 3/8	16	39 3/8	3 3/8	3	3	3 3/8	600	10
060-8024	3/4, 1, 1 1/4	28 3/8	16	39 3/8	3 3/8	3	3	3 3/8	600	15
060-8042	1 1/4, 1 1/2	35 3/8	16	48 3/8	4	3 1/2	3 1/2	3 3/4	680	25
060-8060	1 1/4, 1 1/2	35 3/8	16	52 3/8	4 1/4	3 3/4	4 3/4	4 1/2	750	35



K-1080 Headache Ball Assembly with thimble cap.

Part No.	Wire Rope Size	a	b	c	d	e	f	g	Wgt.	Max. Load Tons
060-8104	3/4	15	7	21 1/8	1 3/8	1 1/8	1 1/8	1 3/4	65	5
060-8122	3/4	15	8.5	21 1/8	1 3/8	1 1/8	1 1/8	1 3/4	100	5
060-8140	3/4	18 3/8	9	21 3/8	2 1/2	2 1/4	2 1/4	2 3/4	130	8.5
060-0610	3/4	18 3/8	10	27 3/8	2 1/2	2 1/4	2 1/4	2 3/4	170	8.5
060-0638	3/4	19 3/8	11	28 3/8	2 1/2	2 1/4	2 1/4	2 3/4	215	8.5
060-0656	3/4	19 3/8	12	28 3/8	2 1/2	2 1/4	2 1/4	2 3/4	265	8.5
060-0674	3/4	20 3/8	13	29 3/8	2 1/2	2 1/4	2 1/4	2 3/4	332	8.5
060-0692	1	23 3/8	13	34 3/8	3 3/8	3	3	3 3/8	366	10
060-0718	1	23 3/8	13	34 3/8	3 3/8	3	3	3 3/8	366	15
060-0736	1 1/4, 1 1/2	27 3/8	13	39 3/8	4	3 1/2	3 1/2	3 3/4	420	25
060-2217	1 1/4, 1 1/2	27 3/8	13	44 3/8	4 1/4	3 3/4	4 3/4	4 1/2	500	35
060-2235	1	26 3/8	16	36 3/8	3 3/8	3	3	3 3/8	600	10
060-2253	1	26 3/8	16	36 3/8	3 3/8	3	3	3 3/8	600	15
060-2271	1 1/4, 1 1/2	29 3/8	16	41 3/8	4	3 1/2	3 1/2	3 3/4	650	25
060-2315	1 1/4, 1 1/2	29 3/8	16	45 3/8	4 1/4	3 3/4	4 3/4	4 1/2	720	35

