



EQUIPMENT TABLES

Metric Units

Equipment Number		Equipment Letter					Stud Link Chain Cables for Bower Anchor				Stockless Bower Anchor	
Exceeding	Not Exceeding	NK	LR	AB	NV	BV	Total Length	Diameter			Number	Weight per Anchor
								Mild Steel (Grade 1)	Special Quality Steel (Grade 2)	Extra Special Quality Steel (Grade 3)		
							metres	mm	mm	mm		kg
50	70	A1	A	U1	—	—	220	14	12.5	—	2	180
70	90	A2	B	U2	—	—	220	16	14	—	2	240
90	110	A3	C	U3	—	—	247.5	17.5	16	—	2	300
110	130	A4	D	U4	—	—	247.5	19	17.5	—	2	360
130	150	A5	E	U5	—	—	275	20.5	17.5	—	2	420
150	175	B1	F	U6	—	—	275	22	19	—	2	480
175	205	B2	G	U7	—	—	302.5	24	20.5	—	2	570
205	240	B3	H	U8	—	—	302.5	26	22	—	3	660
240	280	B4	I	U9	—	—	330	28	24	—	3	780
280	320	B5	J	U10	—	—	357.5	30	26	—	3	900
320	360	C1	K	U11	—	—	357.5	32	28	—	3	1020
360	400	C2	L	U12	—	—	385	34	30	—	3	1140
400	450	C3	M	U13	—	—	385	36	32	—	3	1290
450	500	C4	N	U14	—	—	412.5	38	34	—	3	1440
500	550	C5	O	U15	—	—	412.5	40	34	—	3	1590
550	600	D1	P	U16	—	—	440	42	36	—	3	1740
600	660	D2	Q	U17	—	—	440	44	38	—	3	1920
660	720	D3	R	U18	—	—	440	46	40	—	3	2100
720	780	D4	S	U19	—	—	467.5	48	42	—	3	2280
780	840	D5	T	U20	—	—	467.5	50	44	—	3	2460
840	910	E1	U	U21	—	—	467.5	52	46	40	3	2640
910	980	E2	V	U22	—	—	495	54	48	42	3	2850
980	1060	E3	W	U23	—	—	495	56	50	44	3	3060
1060	1140	E4	X	U24	—	—	495	58	50	46	3	3300
1140	1220	E5	Y	U25	—	—	522.5	60	52	46	3	3540
1220	1300	F1	Z	U26	—	—	522.5	62	54	48	3	3780
1300	1380	F2	A†	U27	—	—	522.5	64	56	50	3	4050
1380	1480	F3	B†	U28	—	—	550	66	58	50	3	4320
1480	1570	F4	C†	U29	—	—	550	68	60	52	3	4590
1570	1670	F5	D†	U30	—	—	550	70	62	54	3	4890
1670	1790	G1	E†	U31	—	—	577.5	73	64	56	3	5250
1790	1930	G2	F†	U32	—	—	577.5	76	66	58	3	5610
1930	2080	G3	G†	U33	—	—	577.5	78	68	60	3	6000
2080	2230	G4	H†	U34	—	—	605	81	70	62	3	6450
2230	2380	G5	I†	U35	—	—	605	84	73	64	3	6900
2380	2530	H1	J†	U36	—	—	605	87	76	66	3	7350
2530	2700	H2	K†	U37	—	—	632.5	90	78	68	3	7800
2700	2870	H3	L†	U38	—	—	632.5	92	81	70	3	8300
2870	3040	H4	M†	U39	—	—	632.5	95	84	73	3	8700
3040	3210	H5	N†	U40	—	—	660	97	84	76	3	9300
3210	3400	J1	O†	U41	—	—	660	100	87	78	3	9900
3400	3600	J2	P†	U42	—	—	660	102	90	78	3	10500
3600	3800	J3	Q†	U43	—	—	687.5	105	92	81	3	11100
3800	4000	J4	R†	U44	—	—	687.5	107	95	84	3	11700
4000	4200	J5	S†	U45	—	—	687.5	111	97	87	3	12300
4200	4400	K1	T†	U46	—	—	715	114	100	87	3	12900
4400	4600	K2	U†	U47	—	—	715	117	102	90	3	13500
4600	4800	K3	V†	U48	—	—	715	120	105	92	3	14100
4800	5000	K4	W†	U49	—	—	742.5	122	107	95	3	14700
5000	5200	K5	X†	U50	—	—	742.5	124	111	97	3	15400
5200	5500	L1	Y†	U51	—	—	742.5	127	111	97	3	16100
5500	5800	L2	Z†	U52	—	—	742.5	130	114	100	3	16900
5800	6100	L3	A*	U53	—	—	742.5	132	117	102	3	17800
6100	6500	L4	B*	U54	—	—	742.5	—	120	107	3	18800
6500	6900	L5	C*	U55	—	—	770	—	124	111	3	20000
6900	7400	M1	D*	U56	—	—	770	—	127	114	3	21500
7400	7900	M2	E*	U57	—	—	770	—	132	117	3	23000
7900	8400	M3	F*	U58	—	—	770	—	137	122	3	24500
8400	8900	M4	G*	U59	—	—	770	—	142	127	3	26000
8900	9400	M5	H*	U60	—	—	770	—	147	132	3	27500
9400	10000	N1	I*	U61	—	—	770	—	152	132	3	29000
10000	10700			U62	—	—	770	—	—	137	3	31000
10700	11500			U63	—	—	770	—	—	142	3	33000
11500	12400			U64	—	—	770	—	—	147	3	35000
12400	13400			U65	—	—	770	—	—	152	3	38500
13400	14600			U66	—	—	770	—	—	157	3	42000
14600				U67	—	—	770	—	—	162	3	46000