



MACHINE CHAIN



This is a short link welded chain used where strength, compactness and extra flexibility is needed: tailgates, agricultural implements, and overhead doors.

Straight Link Machine Chain Specifications

Trade Size	Material Size, Inches	Nominal Inside Link Dimensions, Inches		Maximum Length 100 Links, Inches	Maximum Weight Per 100 Ft., Lbs.	Working Load Limit, Lbs.
		Length	Width			
4	.120	.55	.22	57	13	215
2	.148	.61	.27	63	20	325
1	.162	.63	.29	66	24	390
1/0	.177	.74	.32	77	28	465
2/0	.192	.78	.35	81	33	545
3/0	.207	.85	.37	88	38	635
4/0	.218	.95	.40	99	42	750
5/0	.250	1.07	.45	111	56	925



This chain is made from Straight Link, each link being twisted to make it lie more flat and compact.

Twist Link Machine Chain Specifications

Trade Size	Material Size, Inches	Nominal Inside Link Dimensions, Inches		Maximum Length 100 Links, Inches	Maximum Weight Per 100 Ft., Lbs.	Working Load Limit, Lbs.
		Length	Width			
4	.120	.52	.18	54	14	205
2	.148	.58	.22	60	21	310
1	.162	.59	.25	61	26	370
1/0	.177	.68	.27	71	30	440
2/0	.192	.73	.29	76	35	520
3/0	.207	.80	.32	83	42	605
4/0	.218	.89	.34	93	46	670
5/0	.250	1.00	.38	104	59	880

Finish: Bright, Zinc Plated or Hot Galvanized can be case hardened if specified.