



COIL CHAIN



Coil Chain has longer inside length than proof coil and Machine Chain, and is less flexible. It is used as animal tie-out chain, agricultural implement chain, and platform guard chain, etc.

Straight Link (Long Link) Coil Chain Specifications

Trade Size	Material Size, Inches	Nominal Inside Link Dimensions, Inches		Maximum Length 100 Links, Inches	Maximum Weight Per 100 Ft., Lbs.	Working Load Limit, Lbs.
		Length	Width			
4	.120	1.11	.22	115	10.4	250
2	.148	1.18	.27	123	16	310
1	.162	1.25	.29	130	20	370
1/0	.177	1.25	.32	130	24	440
2/0	.192	1.26	.35	131	28	520
3/0	.207	1.30	.37	135	33	605
4/0	.218	1.39	.39	145	36	670
5/0	.250	1.52	.45	158	48	880



This chain is made from straight link. Each link is twisted to make it lie more flat and compact

Twist Link Coil Chain Specifications

Trade Size	Material Size, Inches	Nominal Inside Link Dimensions, Inches		Maximum Length 100 Links, Inches	Maximum Weight Per 100 Ft., Lbs.	Working Load Limit, Lbs.
		Length	Width			
4	.120	1.09	.19	113	10.4	195
2	.148	1.15	.23	120	17	295
1	.162	1.22	.26	127	21	350
1/0	.177	1.22	.28	127	25	415
2/0	.192	1.24	.30	129	29	495
3/0	.207	1.26	.33	131	34	575
4/0	.218	1.34	.34	139	37	635
5/0	.250	1.47	.39	153	50	835

Finish: Bright, Zinc Plated or Hot Galvanized. Can be case hardened if specified.