



W.J. KEATING LIMITED

CHAIN SLINGS

MONEL, INCONEL, NICKEL, HASTELLOY, STAINLESS STEEL,
TIMKEN ALLOY 16-25-6, AND NIONEL

LINK SPECIFICATIONS, SHOWING SAFE LOADS FOR MONEL CHAIN (factor of safety is 6)

SIZE	INSIDE LENGTH	INSIDE WIDTH	LINK PER FT.	WEIGHT PER FT.	PROOF TEST	
------	---------------	--------------	--------------	----------------	------------	--

SINGLE SLING CHAIN, RECOMMENDED ASSEMBLY

ALL DIMENSIONS IN INCHES

CHAIN SIZE	CONN. LINK	RINGS		PEAR SHAPED END LINKS				SLIP HOOKS			GRAB HOOKS		
		A	B	A	B	C	D	A	B	C	A	B	C
1/4	3/8	1/2	3	1/2	1 1/2	3 1/2	6	7/16	1	2 3/8	7/16	13/32	2 1/4
5/16	3/8	1/2	3	1 1/2	1 1/2	3 1/2	6	1/2	1 1/8	3 3/8	1/2	15/32	2 3/8
3/8	1/2	3/4	4	5/8	1 1/2	3 1/2	6	9/16	1 1/4	3 7/8	9/16	1/2	2 1/2
7/16	1/2	3/4	4	3/4	1 1/2	3 1/2	6	5/8	1 3/8	3 1/2	5/8	19/32	2 1/2
1/2	5/8	7/8	4	7/8	1 1/2	3 1/2	6	11/16	1 5/8	4 1/4	11/16	21/32	4 3/8
9/16	5/8	1	4	1	1 1/2	3 1/2	6	13/16	1 3/4	5 1/4	13/16	3/4	4 3/4
5/8	3/4	1 1/8	5	1	2	4	8	13/16	1 3/4	5 1/4	13/16	3/4	4 3/4
11/16	3/4	1 1/8	5	1 1/8	2	4	8	15/16	2 1/8	5 3/8	15/16	29/32	5 1/8
3/4	7/8	1 1/4	6	1 1/4	2	4	8	15/16	2 1/8	5 3/8	15/16	29/32	5 1/8
13/16	7/8	1 3/8	6	1 3/8	2	4	8	1 1/8	2 3/8	8 1/8	1 1/8	1 1/8	6 1/8
7/8	1	1 1/2	6	1 1/2	3	6	12	1 1/8	2 3/8	8 1/8	1 1/8	1 1/8	6 1/8
15/16	1	1 1/2	6	1 3/4	3	6	12	1 7/8	2 7/8	9 1/2	1 7/8	1 3/4	7 1/2
1	1 1/8	1 3/4	7	1 3/4	3	6	12	1 7/8	2 7/8	9 1/2	1 7/8	1 3/4	7 1/2
1 1/8	1 1/4	1 3/4	8	1 3/4	3	6	12	(Special)			(Special)		
1 1/4	1 3/8	2	9	2	3 1/2	7	14	"			"		