



Regular Diamond & Oval Wire Rope Blocks

These blocks are available with iron or steel sheaves and drop forged fittings. They feature bronze self-lubricating bushings or grooved bronze bushings which are pressure grease lubricated. Available with either painted or galvanized finish.

Single
K-2011



Double
K-2012



Triple
K-2013



Single
K-2141



Double
K-2142



Triple
K-2143



Specifications

Block Size, Inches		4	6	8	10	12
Diameter Rope, Inches		$\frac{3}{8}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{5}{8}$	$\frac{5}{8}$
Sheave Size, Inches	O.D.	4	6	8	10	12
	Rim	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{4}$	$1\frac{1}{2}$
	Ctr. Pin Dia.	$\frac{1}{2}$	$\frac{3}{4}$	$\frac{7}{8}$	$\frac{7}{8}$	1
Weight in Pounds	Single	8	16	26	36	58
	Double	11	24	38	58	82
	Triple	14	32	55	70	128
Working Load Limit*, Tons	Single	1	2	$2\frac{1}{2}$	3	4
	Double	$1\frac{1}{2}$	$2\frac{1}{2}$	$3\frac{1}{2}$	$4\frac{1}{2}$	6
	Triple	2	3	$4\frac{1}{2}$	6	7

Fittings



Swivel Hook,
Fitting "H"

Block Size, Inches	4	6	8	10	12
--------------------	---	---	---	----	----

Stock Numbers for Swivel Hook "H"

Self-lube Bushings, Iron Sheaves, Painted	Diamond	Single	928-0413	928-0613	928-0813	928-1013	928-1213	K-2011
		Double	928-1913	928-2113	928-2313	928-2513	928-2713	K-2012
		Triple	928-3513	928-3713	928-3913	928-4113	928-4313	K-2013
	Oval	Single	927-0413	927-0613	927-0813	927-1013	927-1213	K-2111
		Double	927-1913	927-2113	927-2313	927-2513	927-2713	K-2112
		Triple	927-3513	927-3713	927-3913	927-4113	927-4313	K-2113
Self-lube Bushings, Steel Sheaves, Painted	Diamond	Single	928-0423	928-0623	928-0823	928-1023	928-1223	K-2011
		Double	928-1923	928-2123	928-2323	928-2523	928-2723	K-2012
		Triple	928-3523	928-3723	928-3923	928-4123	928-4323	K-2013
	Oval	Single	927-0423	927-0623	927-0823	927-1023	927-1223	K-2111
		Double	927-1923	927-2123	927-2323	927-2523	927-2723	K-2112
		Triple	927-3523	927-3723	927-3923	927-4123	927-4323	K-2113

continued