



Heavy Blocks for Wire Rope

These galvanized blocks have steel sheaves, ball and roller bearings, and bronze bushings with either self-lubrication or pressure grease lubrication. All fittings are drop forged.



Single
K-2241



Double
K-2242



Triple
K-2243

Specifications

Block Size, Inches		6	8	10
Rope Diameter, Inches		3/8 - 1/2	1/2 - 5/8	5/8
Sheave Size, Inches	O.D.	6	8	10
	Rim	1	1 1/4	1 1/4
	Ctr. Pin Dia.	3/4	7/8	1
Weight in Pounds	Single	23	40	51
	Double	34	54	75
	Triple	48	70	105
Working Load Limit*, Tons	Single	2 1/2	3 1/2	4
	Double	3	6	7
	Triple	4	7	8

Fittings

Stock Numbers for Swivel Hook "H"

K-2211	Self-	Single	729-0623	729-0823	729-1023
K-2212	Lubricated	Double	729-2123	729-2323	729-2523
K-2213	Bushings	Triple	729-3723	729-3923	729-4123
	Pressure Grease Lubricated Bushings	Single	Made to Order		
		Double			
		Triple			

Swivel Hook, Fitting "H"

Stock Numbers for Round Pin Chain Shackle "L"

K-2241	Self-	Single	729-0624	729-0824	729-1024
K-2242	Lubricated	Double	729-2124	729-2324	729-2524
K-2243	Bushings	Triple	729-3724	729-3924	729-4124
	Pressure Grease Lubricated Bushings	Single	Made to Order		
		Double			
		Triple			

Round Chain Shackle, Fitting "L"