



SMALL ROPES "BETTER" COMMERCIAL QUALITY PREFORMED — STEEL — CABLE SPECIFICATIONS

Diameter in Inches	Diameter in Millimeters	Construction	Weight in Lbs. Per M/FL	GALVANIZED STAINLESS STEEL	
				Breaking Strength in Lbs.	Breaking Strength in Lbs.
3/64	1.2	1x7	5.2	375	375
3/64	1.2	1x19	5.5	375	375
3/64	1.2	7x7	4.2	270	270
1/16	1.6	1x7	8.5	500	500
1/16	1.6	1x19	8.5	500	500
1/16	1.6	7x7	7.5	480	480
1/16	1.6	7x19	6.6	Stainless only.	480
5/64	2	1x7	14.0	800	800
5/64	2	1x19	14.2	800	800
5/64	2	7x7	11.8	650	650
3/32	2.5	1x7	20.8	1,200	1,200
3/32	2.5	1x19	20	1,200	1,200
3/32	2.5	7x7	16	920	920
3/32	2.5	7x19	16	1,000	920
1/8	3.2	1x7	32	2,100	2,100
1/8	3.2	1x19	35	2,100	2,100
1/8	3.2	7x7	28.5	1,700	1,700
1/8	3.2	7x19	29	2,000	1,760
5/32	4	1x7	51	3,300	3,300
5/32	4	1x19	55	3,300	3,300
5/32	4	7x7	43	2,600	2,400
5/32	4	7x19	45	2,800	2,400
3/16	5	1x7	73	4,700	4,700
3/16	5	1x19	77	4,700	4,700
3/16	5	7x7	62	3,700	3,700
3/16	5	7x19	65	4,200	3,700
7/32	5.5	1x7	98	5,400	5,400
7/32	5.5	1x19	102	6,300	6,300
7/32	5.5	7x7	83	4,800	4,800
7/32	5.5	7x19	86	5,600	5,000
1/4	6.5	1x7	121	6,650	6,650
1/4	6.5	1x19	135	8,200	8,200
1/4	6.5	7x7	106	6,100	6,100
1/4	6.5	7x19	110	7,000	6,400
9/32	7.5	1x19	170	9,900	9,900
9/32	7.5	7x7	134	7,600	7,600
9/32	7.5	7x19	139	8,000	7,800
5/16	8	1x19	210	12,500	12,500
5/16	8	7x7	167	9,200	9,000
5/16	8	7x19	173	9,800	9,000
3/8	9.5	1x19	300	18,000	17,500
3/8	9.5	7x7	236	13,100	12,000
3/8	9.5	7x19	243	14,400	12,000
7/16	11	6x19IWRC	356	17,600	16,300
1/2	12.7	6x19IWRC	458	22,800	22,800
9/16	14.5	6x19IWRC	590	26,100	28,500
5/8	16	6x19IWRC	715	35,200	35,000
3/4	19	6x19IWRC	1,052	46,000	49,600