



TYPE 305 PREFORMED NON-MAGNETIC STAINLESS STEEL CABLE

Type 305 Stainless Steel Cable is manufactured to meet U.S. Government Military Specification MIL-C-18375A Cable, Steel (Corrosion Resistant Non-Magnetic) Flexible, Preformed (For Aeronautical Use).

(MIL-C-18375A does not include any 1 x 7 or 1 x 19 nor does it include 3/64" 7 x 7 construction. We list these added sizes and constructions for commercial or marine applications only.)

TYPE 316 EXTRA CORROSION RESISTANT STAINLESS STEEL

High strength type 316 Stainless Steel Cable has excellent corrosion resistance yet breaking strengths are almost as high as type 302. If you require high corrosion resistance and high strength, type 316 **high strength** will fill your needs. (Regular type 316 cable priced on request.)

SPECIFICATIONS

Diameter in Inches	Diameter in Millimeters	Construction	Weight in Lbs. Per M/FL	305 Breaking Strength in Lbs.	316 Breaking Strength in Lbs.
3/64	1.2	1x7	5.2	288	361
3/64	1.2	1x19	5.5	250	317
3/64	1.2	7x7	4.2	202	252
1/16	1.6	1x7	8.5	405	490
1/16	1.6	1x19	8.5	385	482
1/16	1.6	7x7	7.5	360	455
1/16	1.6	7x19	6.6	360	446
5/64	2	1x7	14.0	680	784
5/64	2	1x19	14.2	625	770
5/64	2	7x7	11.8	487	615
3/32	2.5	1x7	20.0	1,080	1,175
3/32	2.5	1x19	20	925	1,155
3/32	2.5	7x7	16	700	880
3/32	2.5	7x19	16	785	980
1/8	3.2	1x7	32	1,665	1,830
1/8	3.2	1x19	35	1,785	2,060
1/8	3.2	7x7	28.5	1,310	1,630
1/8	3.2	7x19	29	1,300	1,670
5/32	4	1x7	51	2,700	2,940
5/32	4	1x19	55	3,030	3,235
5/32	4	7x7	43	1,940	2,310
5/32	4	7x19	45	2,000	2,300
3/16	5	1x7	73	3,679	3,990
3/16	5	1x19	77	4,280	4,700
3/16	5	7x7	62	3,145	3,628
3/16	5	7x19	65	2,900	3,585
7/32	5.5	1x7	98	4,914	5,400
7/32	5.5	1x19	102	5,733	6,300
7/32	5.5	7x7	83	4,080	4,700
7/32	5.5	7x19	86	3,800	4,820
1/4	6.5	1x7	121	6,115	6,650
1/4	6.5	1x19	135	7,450	8,200
1/4	6.5	7x7	106	5,370	5,980
1/4	6.5	7x19	110	4,900	5,875
9/32	7.5	1x19	170	9,100	9,900
9/32	7.5	7x7	134	6,512	7,250
9/32	7.5	7x19	139	6,100	7,510
5/16	8	1x19	210	11,500	12,500
5/16	8	7x7	167	8,180	8,920
5/16	8	7x19	173	7,600	8,825
3/8	9.5	1x19	300	16,100	17,500
3/8	9.5	7x7	236	11,460	12,600
3/8	9.5	7x19	243	11,000	11,760
7/16	11	6x19WRC	356	14,900	15,980
1/2	12.7	6x19WRC	458	19,300	20,590
9/16	14.5	6x19WRC	590	24,300	27,930
5/8	16	6x19WRC	715	30,100	34,300
3/4	19	6x19WRC	1,052	42,900	48,600