



PHOSPHOR BRONZE CABLE AND WIRE ROPE

SPECIFICATIONS

		6 x 7		7 x 7		6 x 12	
Diameter		Break	Wgt.	Break	Wgt.	Break	Wgt.
in	mm	Str. Lbs.	M/Fl.	Str. Lbs.	M/Fl.	Str. Lbs.	M/Fl.
1/32	.8	40	1.8	43	2		
3/64	1.2	85	4.1	90	4.4		
1/16	1.6	150	7	170	8.5		
3/32	2.5	340	16	375	18		
1/8	3.2	600	28	660	32		
5/32	4	910	44	1,000	48		
3/16	5	1,320	63	1,450	70		
1/4	6.5	2,280	106			1,470	73
5/16	8	3,520	170			2,270	117
3/8	9.5	5,000	235			3,230	170
7/16	11	6,750	322			4,380	230
1/2	12.7	8,680	420			5,650	290
9/16	14.3	10,800	≈ 530			7,100	370
5/8	15.9	13,200	656			8,740	460
3/4	19.1	18,900	945			12,250	660
		6 x 19		7 x 19		6 x 42	
3/32	2.5					190	12.5
1/8	3.2	615	29	660	35	335	20
5/32	4	915	46				
3/16	5	1,370	66	1,470	70	760	45
1/4	6.5	2,380	112	2,560	124	1,350	80
5/16	8	3,670	175	3,950	195	2,070	120
3/8	9.5	5,240	252	5,600	270	2,960	180
7/16	11	7,080	343			4,020	240
1/2	12.7	9,210	450			5,190	305
9/16	14.3	11,500	570			6,500	390
5/8	15.9	14,150	700			8,000	480
3/4	19.1	19,960	1,010			11,400	690
		8 x 19					
1/4	6.5	2,050	101				
5/16	8	3,160	157				
3/8	9.5	4,510	226				
7/16	11	6,060	310				
1/2	12.7	8,100	403				
9/16	14.3	9,890	509				
5/8	15.9	12,500	630				