



Medium Construction Blocks with Shackles

All blocks are made single, double, triple and quadruple with either oval or diamond shells. They have grooved bronze bushings, pressure grease lubrication or roller bearings. Blocks are galvanized, and have steel sheaves for $\frac{3}{4}$ " diameter wire rope.



Single
K-7641 Oval
K-7741 Diamond



Double
K-7642 Oval
K-7742 Diamond



Quadruple
K-7643 Oval
K-7743 Diamond

Specifications

Sheave Dia., Inches	Working Load Limit*, Tons				Weight in Pounds			
	Single	Double	Triple	Quad.	Single	Double	Triple	Quad.
6	7½	10	12½	15	25	41	59	75
8	7½	10	12½	15	36	52	66	85
10	7½	10	12½	15	44	68	87	100
12	7½	10	12½	15	51	77	102	125
14	7½	10	12½	15	72	112	152	175

Stock Numbers for Oval Blocks

Sheave Dia., Inches	Grooved Bronze Bushed				Roller Bearing			
	K-7641 Single	K-7642 Double	K-7643 Triple	K-7644 Quad.	K-7641 Single	K-7642 Double	K-7643 Triple	K-7644 Quad.
6	942-0111	942-0211	942-0311	942-0411	942-0131	942-0231	942-0331	942-0431
8	942-0112	942-0212	942-0312	942-0412	942-0132	942-0232	942-0332	942-0432
10	942-0113	942-0213	942-0313	942-0413	942-0133	942-0233	942-0333	942-0433
12	942-0114	942-0214	942-0314	942-0414	942-0134	942-0234	942-0334	942-0434
14	942-0115	942-0215	942-0315	942-0415	942-0135	942-0235	942-0335	942-0435

Stock Numbers for Diamond Blocks

Sheave Dia., Inches	Grooved Bronze Bushed				Roller Bearing			
	K-7741 Single	K-7742 Double	K-7743 Triple	K-7744 Quad.	K-7741 Single	K-7742 Double	K-7743 Triple	K-7744 Quad.
6	942-5111	942-5211	942-5311	942-5411	942-5131	942-5231	942-5331	942-5431
8	942-5112	942-5212	942-5312	942-5412	942-5132	942-5232	942-5332	942-5432
10	942-5113	942-5213	942-5313	942-5413	942-5133	942-5233	942-5333	942-5433
12	942-5114	942-5214	942-5314	942-5414	942-5134	942-5234	942-5334	942-5434
14	942-5115	942-5215	942-5315	942-5415	942-5135	942-5235	942-5335	942-5435

Ultimate load is four times Working Load Limit.
All Working Load Limits are Resultant Working Load Limits.