



Technical drawing of a 3100 Series Cable Assembly. The drawing shows a side view of the assembly with various dimensions and labels. Key components and dimensions include:

- Dimensions:**
 - 58**: Distance from the left end to the first fitting.
 - 8**: Distance from the first fitting to the second fitting.
 - 8**: Distance from the second fitting to the third fitting.
 - B**: Distance from the third fitting to the fourth fitting.
 - 1 1/3 FULL THREAD**: Length of the threaded section.
 - 5/32**: Distance from the fourth fitting to the fifth fitting.
 - 125**: Distance from the fifth fitting to the sixth fitting.
 - D**: Distance from the sixth fitting to the seventh fitting.
 - 8**: Distance from the seventh fitting to the eighth fitting.
 - 8**: Distance from the eighth fitting to the ninth fitting.
 - 68**: Distance from the ninth fitting to the end.
 - CABLE LENGTH**: Total length of the cable assembly.
 - MID-TRAVEL**: Distance from the first fitting to the fourth fitting.
- Labels:**
 - 10-32 UNF-2A**: Thread specification for the first and ninth fittings.
 - END FITTING BULKHEAD SWIVEL**: Label for the fourth fitting.
 - 7-16-20 UNF-2A (TYP)**: Thread specification for the fifth fitting.
 - CONDUIT 3/12 DIA.**: Label for the conduit section.
 - CABLE SIZE 075 SOLID CORE**: Label for the cable section.
 - END FITTING CLAMP SWIVEL**: Label for the sixth fitting.
 - 3100 SERIES**: Model name.

302