





Lead Blocks


These blocks are all *Made to Order*. They can be furnished with iron or steel sheaves and a painted or galvanized finish. Choose either bronze, self-lubricating bushing; or pressure grease lubricated, bronze or tapered roller bearings.



Vertical
K-6501



Horizontal
K-6502



Block Size, Inches		3	4	6	8	10	12	14
Wire Rope Diameter, Inches		$\frac{3}{8}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{5}{8}$	$\frac{5}{8}$	$\frac{3}{4}$	$\frac{7}{8}$
Sheave Size, Inches	O.D.	3	4	6	8	10	12	14
	Rim	$\frac{3}{4}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{4}$	$1\frac{1}{2}$	$1\frac{1}{2}$
	Pin	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{3}{4}$	$\frac{7}{8}$	1	$1\frac{1}{8}$	$1\frac{1}{4}$
Dimensions, Inches, Fig. 4152	A	$3\frac{1}{2}$	$4\frac{1}{2}$	$6\frac{1}{2}$	$8\frac{7}{8}$	12	14	$15\frac{1}{2}$
	B	$3\frac{3}{4}$	$3\frac{3}{4}$	$4\frac{1}{2}$	5	5	$5\frac{3}{4}$	$6\frac{1}{2}$
	C	5	$5\frac{7}{8}$	$8\frac{1}{8}$	$10\frac{3}{4}$	$12\frac{1}{2}$	$15\frac{1}{4}$	$17\frac{1}{2}$
Dimensions, Inches, Fig. 4153	D	$7\frac{1}{4}$	$8\frac{1}{4}$	$11\frac{3}{4}$	$14\frac{1}{2}$	$16\frac{1}{2}$	$18\frac{1}{2}$	$21\frac{1}{2}$
	E	$4\frac{1}{2}$	$5\frac{1}{2}$	$7\frac{1}{2}$	10	12	14	15
	F	$1\frac{1}{4}$	$1\frac{1}{4}$	$1\frac{1}{2}$	$1\frac{13}{16}$	$1\frac{15}{16}$	$2\frac{1}{8}$	$2\frac{1}{4}$
Resultant Working Load Limit*, Tons		1	1	2	$2\frac{1}{2}$	3	4	5

Flag Blocks for Wire Rope

These blocks can be supplied with steel sheaves 3" to 30" and cast iron sheaves from 3" to 16". They feature grooved bronze bushings and tapered roller or ball bearings, both pressure grease lubricated.

Figure 4155 swings horizontally on trunnions. The lower trunnion is hollow and permits wire to pass vertically through it, so that the wire remains in the center line of the trunnions. Trunnions have bronze or roller thrust bearings, with pressure grease lubrication.



K-6503



K-6504

*Warning: Do not exceed the Working Load Limit.