



ELECTRIC WINCHES

Shur-Worm 1500 Lbs. to 3000 Lbs.

Convert to Power

For heavy duty hand or convert to power use. Same features as hand winches, but special anti-friction bearings make these models convertible to intermittent power. (Not furnished with free spooling.)

Specifications:

MODEL	CAPACITY (LBS.)		LINE SPEED FPM	GEAR RATIO	HORSE-POWER	DRUM CAPACITY				SHIPPING WEIGHT (LBS.)
	HAND 1ST LAYER	POWER 2ND LAYER				1/8"	3/16"	1/4"	5/16"	
K-4060	1500	750	10	20:1	3/4	120	60	34		21
K-4061	1500	750	10	20:1	3/4	240	120	67		21 1/2
K-4062	3000	1500	11	30:1	1 1/2	560	253	135	96	51

Electric Worm Gear Winch



Electric Winches 750 Lbs. to 2000 Lbs. Worm Gear

Features: Automatic self-locking machine-cut gears, fully enclosed with anti-friction bearings. Fully reversing motors are 15-minute duty.

Specifications:

MODEL		LINE PULL 2ND LAYER (LBS)	LINE SPEED 2ND LAYER (FPM)	DUTY CYCLE (MIN)	HORSE POWER	MAX. DRUM STORAGE				SHIPPING WEIGHT (LBS)
1/60/115V-230V	3/60/230V-460V					3/16"	1/4"	5/16"	3/8"	
K-4063	K-4064	1000	30	15	1 1/2	253	135	96		117
K-4065	K-4066	1100	20	15	1 1/2	253	135	96		117
K-4067	K-4068	1500	20	15	1 1/2	338	200	122	87	111
K-4069	K-4070	2000	20	10	1 1/2	338	200	122		111
K-4071	K-4072	750	43	15	1 1/2	338	200	122	87	105

12" Drums Available

¹EW and EBT Models are belt driven

²DT models are direct driven