



Marine Specialty Products

Cargo Hoisters with Tapered, Roller Bearings

Designed for wire rope and heavy marine duty. All fittings are drop forged. Block has pressure grease lubrication. The working load limit for cargo hoisters is the line pull, and they are proof tested to 4 times the working load limit.

Specifications

Type of Block		Sheave Dia., Inches	Wire Dia., Inches	Weight in Pounds	Working Load Limit*, Tons
Drop Forged	Regular	14	5/8-1	100	5
		16	5/8-1	135	5
	Super	14	3/4-1	100	10
		16	3/4-1	135	10
Cast Steel	Super	16	3/4-1 1/4	190	10
		18	3/4-1 1/4	220	10



K-8050

Stock Numbers with Various Fittings

Type of Block		P	Q	T	U	Y	Z
14", Drop Forged	Regular	TB739-1451	TB739-1452	TB739-1453	TB739-1454	TB739-1455	TB739-1456
	Super	TB739-2451	TB739-2452	TB739-2453	TB739-2454	TB739-2455	TB739-2456
16", Drop Forged	Regular	TB739-1651	TB739-1652	TB739-1653	TB739-1654	TB739-1655	TB739-1656
	Super	TB739-2651	TB739-2652	TB739-2653	TB739-2654	TB739-2655	TB739-2656
Cast Steel	Super 16"	Made to Order					
	Super 18"						



Fitting "Q"
K-8070



Fitting "T"
K-8060



Fitting "U"
K-8080



Fitting "Y"
K-8080B



Fitting "Z"
K-8070

*Warning: Do not exceed the Working Load Limit.