



ELECTRIC CHAIN HOISTS & END TRUCKS

Specifications for Hook Mount Electric Chain Hoist

Part No.	MODEL	CAPACITY (TONS)	STD LIFT (FT)	LIFTING SPEED (FPM)	AMPS @ 230V	MOTOR 3-PHASE HP/KW	NUMBER CHAIN PARTS	SHIPPING WEIGHT (LBS)
104-1063	BBES003	1/4	10	32	3.7	8/45	1	62
104-1081	BBES005L	1/2-L	10	18	3.7	8/45	2	73
104-1107	BBES005S	1/2-S	10	27	5.2	11/8	1	90
104-1125	BBES010L	1-L	10	14	5.2	11/8	2	103
104-1143	BBES010S	1-S	10	27	8.2	21/5	1	125
104-1161	BBES015	1 1/2	10	34	15.8	4/3	1	220
104-1189	BBES020L	2-L	10	14	8.2	21/5	2	145
104-1205	BBES020S	2-S	10	26	15.8	4/3	1	220
104-1223	BBES025	2 1/2	10	21	15.8	4/3	1	229
104-1269	BBES030	3	10	17	15.8	4/3	2	288
104-1303	BBES050	5	10	11	15.8	4/3	2	306
104-1321	BBES100	10	10	11	31.6	4/3X2	4	682

Capacities Available to 20 Tons

Also Available With Plain, Geared or Motorized Trolley

L = Low Speed; S = Standard Speed

Specifications: Electric powered end trucks — contact factory for push-pull and hand geared specifications

MODEL ¹	CAPACITY (tons)	MAX. SPAN (ft.)	TRAVEL ² SPEED (fpm)	GUIDE WHEEL BASE (ins.)	I-BEAM FLANGE WIDTH (ins.)	ASCE RUNWAY RAIL SIZE (lbs. per ft.)	SHIPPING WEIGHT (lbs.)
UNDER RUNNING — SIDE ROLLER							
BB (R, Q or T) L330	3	40	40, 60, 110	47 1/4	3-6	—	380
BB (R, Q or T) L350	3-5	40-32	40, 60, 110	47 1/4	4-5	—	580
BB (R, Q or T) L350-1	5	40	40, 60, 110	74	5-7.5	—	830
BB (R, Q or T) L350-2	5	48	40, 60, 110	86	5-7.5	—	890
UNDER RUNNING — CONVENTIONAL							
BBC (P, Q, T or V) L750-1*	7 1/2	40	60, 80, 115, 140	60	5-7.5	—	1000
BBC (P, Q, T or V) L750-2*	7 1/2	48	60, 80, 115, 140	72	5-7.5	—	1060
TOP RUNNING — SIDE ROLLER							
BB (R, Q or T) 0330	3	40	40, 60, 110	47 1/4	—	20, 25, 30	295
BB (R, Q or T) 0630*	3-5	60-40	40, 60, 115	70 1/4	—	35, 45	433
BB (R, Q or T) 0350	3-5	40-32	40, 60, 115	47 1/4	—	35, 45	356
BB (Q, T or V) 0550*	5	60	60, 115, 145	70 1/4	—	40, 45	730
BBQ0411*	10	40	60	59	—	40, 60	1166
BBQ0811*	10	65	60	98 1/4	—	40, 60	1672
BBQ0615*	15	60	60	98 1/4	—	60, 80	3124
TOP RUNNING — CONVENTIONAL							
BBC (R, Q or T) 0350-1	5	40	45, 95, 130	60	—	40	850
BBC (R, Q or T) 0350-2	5	48	45, 95, 130	72	—	40	890
BBC (P, Q, T or V) 0750-1*	7 1/2	40	70, 85, 120, 150	60	—	40	1000
BBC (P, Q, T or V) 0750-2*	7 1/2	48	70, 85, 120, 150	72	—	40	1110
BBC (P, Q, T or V) 0411-1*	10	40	70, 80, 120, 150	60	—	40, 60	1025
BBC (P, Q, T or V) 0411-2*	10	48	70, 80, 120, 150	72	—	40, 60	1110

¹Refers to pair of end trucks.

²FPM Travel speed indicated as follows: R = 40-45, P = 60-70, Q = 80-95, T = 110-130, V = 140-150

*These models plus all side roller models with 120 fpm travel speed include power couplings as standard