



AIR VALVES

Pressure Seated
Brass AIR VALVES
With Pressure Bleed

RA

90° Angle Valve



Outlet—Inlet

1/4" — 1/2"
3/8" — 1/2"
3/8" — 1/2" Control Plate
1/2" — 3/4"
3/4" — 1"

PO

Parallel Port Valve



Outlet—Inlet

3/8" — 1/2"
1/2" — 3/4"
3/4" — 1"
1" — 1 1/4"


SR

Straight Port Valve



Outlet—Inlet

1/4" — 1/4"
3/8" — 3/8"
1/2" — 1/2"
3/4" — 3/4"
1" — 1"



VC-1

Gasket



Neoprene

Size

3/4"

2M

**Double Outlet
Manifolds**



For Valve Inlet Outlet

1/2" — 3/4" 3/4" — 1"
3/4" — 1" 1" — 1"

A

30° Angle Valve



Outlet—Inlet

1/2" — 3/4"
3/4" — 1"

LW

2—Way Outlet Valve



Equipped
with
Alemite Fittings

Valve Size Inlet Size of Outlet

3/8" — 3/4" 3/8" — 3/8"
1/2" — 1" 1/2" — 1/2"
3/4" — 1 1/4" 3/4" — 3/4"



Neutral or Off Position



Exhaust Position



Supply Position

FWL

4—Way Valve



Equipped
with
Alemite Fittings

Valve Size Inlet Size of Outlet

3/8" — 1" 3/8" — 3/8"
1/2" — 1 1/4" 1/2" — 1/2"



Left Hand Supply
Right Hand Exhaust



Neutral or Off Position



Right Hand Supply
Left Hand Exhaust