




## HEAVY DUTY END FITTINGS

### stainless steel thimble to BS 3100/347C17 or equivalent

| Rope size<br>no. | Thimble size<br>mm |      |     |     |     |    |    | Weight (approx)<br>kg |
|------------------|--------------------|------|-----|-----|-----|----|----|-----------------------|
|                  | A                  | B    | C   | D   | E   | F  | G  |                       |
| 12               | 600                | 480  | 180 | 100 | 100 | 15 | 20 | 90                    |
| 15               | 730                | 725  | 210 | 125 | 125 | 15 | 20 | 125                   |
| 18               | 855                | 870  | 250 | 150 | 150 | 20 | 25 | 215                   |
| 21               | 940                | 950  | 270 | 160 | 160 | 20 | 30 | 310                   |
| 24               | 1020               | 1020 | 300 | 180 | 180 | 25 | 30 | 400                   |


Also available in  
NI-RESIST IRON.



### galvanised standard tubular thimble

| Rope size<br>no. | Thimble size<br>mm |     |     |     |     |     |     |    |    |     |     |    | Weight (approx)<br>kg |
|------------------|--------------------|-----|-----|-----|-----|-----|-----|----|----|-----|-----|----|-----------------------|
|                  | A                  | B   | C   | D   | E   | F   | H   | K  | M  | P1  | P2  | R  |                       |
| 12               | 521                | 260 | 420 | 130 | 241 | 194 | 144 | 20 | 50 | 140 | 130 | 60 | 45                    |
| 15               | 625                | 312 | 510 | 150 | 289 | 194 | 144 | 25 | 55 | 168 | 158 | 65 | 76                    |
| 18               | 727                | 368 | 610 | 175 | 340 | 219 | 169 | 30 | 60 | 194 | 183 | 70 | 140                   |
| 21               | 829                | 415 | 740 | 200 | 391 | 229 | 169 | 35 | 75 | 219 | 206 | 75 | 196                   |
| 24               | 930                | 465 | 880 | 225 | 441 | 273 | 201 | 40 | 80 | 245 | 229 | 80 | 320                   |

Pin location (B/C)  
can be adjusted to  
suit individual  
requirements.



### 'D' shackle for tubular thimbles

| Rope size no. | Shackle size mm |     |      |     |     |     |     | Breaking strength tonnes |
|---------------|-----------------|-----|------|-----|-----|-----|-----|--------------------------|
|               | A               | B   | C    | D   | E   | F   | ØG  |                          |
| 15            | 469             | 215 | 670  | 480 | 75  | 70  | 80  | 206                      |
|               | 531             | 215 | 726  | 480 | 101 | 88  | 94  | 320                      |
|               | 557             | 215 | 740  | 480 | 110 | 100 | 108 | 480                      |
| 18            | 559             | 243 | 811  | 565 | 101 | 88  | 94  | 300                      |
|               | 585             | 243 | 825  | 565 | 110 | 100 | 108 | 450                      |
|               | 561             | 243 | 840  | 565 | 105 | 95  | 115 | 675                      |
| 21            | 610             | 268 | 895  | 635 | 110 | 100 | 108 | 400                      |
|               | 586             | 268 | 913  | 635 | 105 | 95  | 115 | 600                      |
|               | 616             | 268 | 950  | 635 | 120 | 110 | 130 | 900                      |
| 24            | 614             | 296 | 988  | 720 | 105 | 95  | 115 | 500                      |
|               | 644             | 296 | 1025 | 720 | 120 | 110 | 130 | 800                      |
|               | 681             | 296 | 1070 | 720 | 135 | 125 | 150 | 1200                     |

### 2-pin connecting shackle for tubular thimbles

| Rope size<br>no. | Shackle size<br>mm |     | Weight (approx)<br>kg |
|------------------|--------------------|-----|-----------------------|
|                  | A                  | B   |                       |
| 12               | 160                | 390 | 142                   |
| 15               | 190                | 430 | 153                   |
| 18               | 215                | 495 | 164                   |
| 21               | 260                | 600 | 180                   |

Available with chain  
positioning bushes.

