



W.J. KEATING LIMITED

	Standard Wire Rope Size	Sheave Size (Dia.)	No. of Sheaves	A	B	C	D	E	F	G	H	Total Weight
				Thickness	Width	Overall Length	Throat Opening w/o Latch	Throat Opening With Latch	Sheave Pin Dia.	Backset Pin Dia.	Plate Thickness	
	1 1/4"	30"	1	14 1/8"	33"	62 1/4"	4"	3 5/8"	5"	2 1/2"	2"	1750
	1 1/4"	30"	1	14 1/8"	33"	65 1 1/8"	4 1/4"	3 3/8"	5"	2 1/2"	2"	1750
	1 1/4"	30"	1	14 7/16"	33"	67 1 1/8"	4 3/8"	4 1/8"	5"	2 1/2"	2"	2000
	1 1/4"	30"	1	14 7/8"	33"	71 3/4"	5 3/4"	5 1/8"	5 1/2"	2 1/2"	2"	2100
	1 1/4"	30"	2	14 7/8"	33"	65 1 1/8"	4 1/4"	3 3/4"	5"	2 1/2"	2"	1900
	1 1/4"	30"	2	14 7/8"	33"	67 1 1/8"	4 1/4"	4 1/4"	5"	2 1/2"	2"	2160
	1 1/4"	30"	2	14 7/8"	33"	71 3/4"	5 3/4"	5 1/8"	5 1/2"	2 1/2"	2"	2250
	1 1/4"	30"	2	14 7/8"	33"	74 3/4"	6 1/2"	5 9/8"	5"	2 1/2"	2"	2500
	1 1/4"	30"	3	19 15/16"	33"	71 3/4"	5 3/4"	5 1/8"	5"	2 1/2"	2"	2735
	1 1/4"	30"	3	19 15/16"	33"	74 3/4"	6 1/4"	5 1/8"	5"	2 1/2"	2"	2835
	1 1/4"	30"	3	19 15/16"	33"	79 7/8"	6 1/2"	5 9/8"	5"	2 1/2"	2"	3175
	1 1/4"	30"	3	19 15/16"	33"	80 7/8"	6"	5 1/2"	5"	2 1/2"	2"	3200
	1 1/4"	30"	2	19 15/16"	33"	80 7/8"	6"	5 1/2"	5"	2 1/2"	2"	3200
	1 1/4"	30"	4	23 5/16"	36"	74 5/16"	6 1/2"	5 7/8"	5"	2 1/2"	2"	3625
	1 1/4"	30"	4	23 5/16"	36"	79 7/8"	6 7/8"	5 3/8"	5"	2 1/2"	2"	3725
	1 1/4"	30"	4	23 5/16"	36"	80 7/8"	6"	5 1/2"	5"	2 1/2"	2"	3825
	1 1/4"	30"	4	23 5/16"	36"	80 7/8"	6"	5 1/2"	5"	2 1/2"	2"	3825
	1 1/4"	30"	4	23 5/16"	36"	88"	6 1/2"	6"	5"	2 1/2"	2"	4200
	1 1/4"	30"	5	28	36"	79 7/8"	6 7/8"	5 3/8"	5"	2 1/2"	2"	4530
	1 1/4"	30"	5	28	36"	86 3/4"	6"	5 1/2"	5"	2 1/2"	2"	4560
	1 1/4"	30"	5	28	36"	88"	6 1/2"	6"	5"	2 1/2"	2"	4700
	1 1/4"	30"	5	30	36"	94 1/4"	7 1/2"	8"	5"	2 1/2"	3"	6400
	1 1/4"	30"	6	31 3/4"	36"	86 3/4"	6"	5 1/2"	5"	2 1/2"	2"	4650
	1 1/4"	30"	6	31 3/4"	36"	89"	6 1/2"	6"	5"	2 1/2"	2"	4900
	1 1/4"	30"	6	31 3/4"	36"	93 1/2"	8"	7 1/8"	5"	2 1/2"	2"	5120
	1 1/4"	30"	6	33 3/4"	36"	94 1/4"	8"	7 1/8"	5"	2 1/2"	3"	6700
	1 1/4"	36"	1	14 7/8"	39"	74 1/4"	4 3/4"	4 1/4"	5"	2 1/2"	2"	2500
	1 1/4"	36"	1	14 7/8"	42 1/2"	80 1 1/8"	6 1/2"	5 7/8"	5"	2 1/2"	2"	2600
	1 1/4"	36"	1	14 7/8"	42 1/2"	86 3/8"	5 9/8"	5 3/8"	5"	2 1/2"	2"	3250
	1 1/4"	36"	2	14 7/8"	42 1/2"	80 1 1/8"	6 1/2"	5 3/8"	5"	2 1/2"	2"	3000
	1 1/4"	36"	2	14 7/8"	42 1/2"	86 3/8"	5 7/8"	5 1/8"	5"	2 1/2"	2"	3450
	1 1/4"	36"	2	14 7/8"	42 1/2"	87 3/8"	6"	5 1/2"	5"	2 1/2"	2"	3600
	1 1/4"	36"	3	19 15/16"	42 1/2"	86 3/8"	5 1/8"	5 3/8"	5"	2 1/2"	2"	3900
	1 1/4"	36"	3	19 15/16"	42 1/2"	87 3/8"	6"	5 1/2"	5"	2 1/2"	2"	3930
	1 1/4"	36"	3	19 15/16"	42 1/2"	87 3/8"	6"	5 1/2"	5"	2 1/2"	2"	3930
	1 1/4"	36"	4	23 5/16"	42 1/2"	86 3/8"	5 7/8"	5 3/8"	5"	2 1/2"	2"	4490
	1 1/4"	36"	4	23 5/16"	42 1/2"	87 3/8"	6"	5 1/2"	5"	2 1/2"	2"	4590
	1 1/4"	36"	4	23 5/16"	42 1/2"	87 3/8"	6"	5 1/2"	5"	2 1/2"	2"	4590
	1 1/4"	36"	4	23 5/16"	42 1/2"	95 1/2"	6 1/2"	6"	5"	2 1/2"	2"	4965
	1 1/4"	36"	5	28	42 1/2"	86 3/8"	5 7/8"	5 3/8"	5"	2 1/2"	2"	5340
	1 1/4"	36"	5	28	42 1/2"	87 7/8"	6"	5 1/2"	5"	2 1/2"	2"	5370
	1 1/4"	36"	5	28	42 1/2"	95 1/2"	6 1/2"	6"	5"	2 1/2"	2"	5600
	1 1/4"	36"	5	30	42 1/2"	100 3/4"	8"	7 1/2"	5"	2 1/2"	3"	7025
	1 1/4"	36"	6	31 3/4"	42 1/2"	87 7/8"	6"	5 1/2"	5"	2 1/2"	2"	5600
	1 1/4"	36"	6	31 3/4"	42 1/2"	95 1/2"	6 1/2"	6"	5"	2 1/2"	2"	5900
	1 1/4"	36"	6	31 3/4"	42 1/2"	99 5/8"	8"	7 1/2"	5"	2 1/2"	2"	6125
	1 1/4"	36"	6	33 3/4"	42 1/2"	100 3/4"	8"	7 1/2"	5"	2 1/2"	2"	7370

(1) Proof Load Limit 74 Tons (2) Proof Load Limit 90 Tons