



LINKS

REPLACEMENT LINKS



- Hot Dipped Galvanized
- Except Alloy
- Forged steel.
- Integral rivets join the two halves — matched lugs distribute the load.
- Meets or exceeds Federal Specifications RR-C-271b Type II.

Part No.		Size Inches	Links Per Box	Overall Dimensions Inches	Inside Dimensions Inches	Safe Working Load — Pounds**		Weight Pounds Per 100
Alloy	C.S.					Alloy	C.S.	
	901-3094	1 1/16	20	1 3/16 x 2 5/32	1 1/16 x 1 1/32	—	800	2.50
	901-3110	1 1/4	10	1 1/2 x 1	3/4 x 7/16	—	1325	6.25
920-8505	901-3138	1 5/16	10	1 11/16 x 1 5/32	1 5/16 x 1 5/32	3000	1950	12.50
920-8605	901-3156	3/8	10	2 1/16 x 1 3/8	1 1/8 x 3/16	4200	2750	20.00
920-8705	901-3174	7/16	10	2 11/32 x 1 17/32	1 3/32 x 1 5/32	5400	3625	27.50
920-8805	901-3192	1/2	10	2 21/32 x 1 23/32	1 15/32 x 2 1/32	7000	4750	37.50
920-9005	901-3236	5/8	10	3 5/16 x 2 3/32	1 13/16 x 2 5/32	10800	7250	72.50
920-9205	901-3254	3/4	10	3 3/8 x 2 1/2	2 1/8 x 1 5/16	15000	10250	122.50
920-9405	901-3272	7/8	In Bulk	4 1/2 x 2 15/16	2 1/2 x 1 1/8	18000	12000	175.00
920-9605	901-3290	*1	In Bulk	5 x 3 5/16	2 3/4 x 1 1/4	24000	15500	250.00
	901-3316	*1 1/8	In Bulk	5 5/8 x 3 11/16	3 1/8 x 1 3/8	—	19500	375.00
	901-3334	*1 1/4	In Bulk	6 1/8 x 4 3/16	3 3/4 x 1 5/8	—	24000	500.00

*Have reinforced rivet holes. All sizes have rivet holes countersunk.

†Have rivets only — no interlocking lugs.

**Ultimate load is four times the Safe Working Load.

PEAR SHAPE REPLACEMENT LINKS



Part No.	Size Inches	Inside Width Small End Inches	Inside Width Large End Inches	Inside Length Inches	Weight Pounds Per 100	Safe Working Load* Pounds
901-3432	3/8	9/16	1 3/16	2	25	1850
901-3450	1/2	1 1/16	1	2 1/2	50	3300
901-3478	5/8	1 3/16	1 1/8	2 3/4	75	5000
901-3496	3/4	1	1 1/4	3 1/8	125	7100
901-3511	7/8	1 1/4	1 1/2	3 11/16	200	9600
QA	1	1 1/4	1 1/2	3 3/8	325	12400
QA	1 1/8	1 3/8	1 5/8	4 1/4	430	15600

- Forged steel.
- Replacement links having larger inside dimensions making it easier to attach hooks or other fittings to the chain.
- Hot Dip Galvanized

*Ultimate Load is four times the Safe Working Load.



DOUBLE CLEVIS LINK

- Designed for linking all popular sizes of chain to rings, end links, eye hooks, pad eyes, tractor eyebolts, etc.
- Pins can be removed with pliers or screwdriver.
- All pins alloy steel.

Part No.	Chain Size Inches	Safe Working Load* Pounds	DIMENSIONS IN INCHES										Weight Pounds Each
			A	B	C	D	E	F	L	N	P	R	
901-3021	1/4	3250	1/2	3/4	1/2	5/16	3/8	3/4	2 13/16	1.47	1.79	1 1/2	.44
901-3049	5/16-3/8	6600	9/16	1	5/8	7/16	15/32	1	3 17/32	1.86	2.38	1 29/32	.81
901-3067	7/16	8750	1 1/16	1 1/8	1 1/16	9/16	19/32	1 3/32	4 1/16	2.12	2.66	2 3/16	1.28
901-3085	1/2	11250	1 3/16	1 1/4	3/4	5/8	2 1/32	1 1/4	4 17/32	2.38	2.91	2 15/32	1.68

All dimensions approximate and subject to minor changes without notice.

*Ultimate load is 3.2 times the safe working load.