



W.J. KEATING LIMITED

FORGED SHACKLES



Screw pin anchor shackles meet Federal Specification RR-C-271b Type IV Class 1.

K-1005

- Safe Working Load permanently shown on every shackle.
- Forged, Quenched and Tempered, with alloy pins.
- Capacities $\frac{1}{2}$ thru 150 tons.
- Shackles can be furnished proof tested with certificates per requirements of A.B.S. and/or I.C.G.B. Charges for proof testing and certification available on request.
- Hot Dip Galvanized or Self Colored



Round pin anchor shackles meet Federal Specification RR-C-271b Type IV Class 4.

K-1006

ANCHOR SHACKLES

Part No. Screw Pin	Part No. Round Pin	Safe Working Load Tons	Nominal Shackle Size Inches	DIMENSIONS IN INCHES							Weight Pounds Each	
				Inside Length	Inside Width		Diameter		Tolerance Plus or Minus			
					at Pin	at Bow	Pin	Outside of Eye	Length	Width	213	209
901-8357	—	1/2	3/16	7/8	3/8	1 1/16	1/4	9/16	± 1/16	± 1/16	—	.05
901-8375	901-8017	1/2	1/4	1 1/8	1/2	29/32	3/16	1 1/16	± 1/16	± 1/16	13	10
901-8393	901-8035	3/4	5/16	1 7/32	17/32	27/32	3/8	1 3/16	± 1/16	± 1/16	18	19
901-8419	901-8071	1	3/8	1 7/8	21/32	1 1/32	7/16	1 31/32	± 1/16	± 1/16	25	25
901-8437	901-8099	1 1/2	7/16	1 11/16	23/32	1 5/32	1/2	1 1/16	± 1/16	± 1/16	38	50
901-8455	901-8115	2	1/2	1 3/4	1 13/16	1 15/16	3/8	1 3/16	± 1/16	± 1/16	56	75
901-8473	901-8133	3 1/4	3/8	2 3/8	1 1/16	1 11/16	3/8	1 5/16	± 1/16	± 1/16	125	144
901-8491	901-8151	4 3/4	3/8	2 13/16	1 1/4	2	3/8	1 7/16	± 1/16	± 1/16	232	225
901-8516	901-8179	6 1/2	7/8	3 5/16	1 7/16	2 9/32	1	2 1/8	± 1/16	± 1/16	340	350
901-8534	901-8197	8 1/2	1	3 3/4	1 11/16	2 11/16	1 1/8	2 3/8	± 1/16	± 1/16	500	500
901-8552	901-8213	9 1/2	1 1/8	4 1/4	1 13/16	2 29/32	1 1/4	2 5/8	± 1/16	± 1/16	697	725
901-8570	901-8231	12	1 1/4	4 11/16	2 1/32	3 1/4	1 3/8	3	± 1/16	± 1/16	1013	975
901-8598	901-8259	13 1/2	1 3/8	5 1/16	2 3/4	3 1/2	1 1/2	3 5/16	± 1/16	± 1/16	1325	1325
901-8614	901-8277	17	1 1/2	5 3/4	2 5/8	3 3/8	1 3/4	3 3/8	± 1/16	± 1/16	1725	1770
901-8632	901-8295	25	1 3/4	7	2 3/8	5	2	4 1/16	± 1/16	± 1/16	2946	3038
901-8650	—	35	2	7 3/4	3 3/4	5 3/4	2 1/2	5	± 1/16	± 1/16	4575	4500
901-8678	—	55	2 1/2	10 1/2	4 3/8	7 1/4	2 3/4	6	± 1/16	± 1/16	—	8575



Trawling shackle with thin square head with screw pin.

K-1014

TRAWLING SHACKLES Self Colored only

Part No.	Safe Working Load Tons	Nominal Shackle Size Inches	DIMENSIONS IN INCHES						Weight Pounds Each
			Inside Length	Inside Width at Pin	Diameter		Tolerances Plus or Minus		
					Pin	Outside of Eye	Length	Width	
901-8703	2	1/2	1 5/8	13/16	5/8	1 3/16	1/8	1/16	.75
901-8721	3 1/4	5/8	2	1 1/16	3/4	1 9/16	1/8	1/16	1.24
901-8749	4 3/4	3/4	2 3/8	1 1/4	7/8	1 7/8	1/4	1/16	2.25
901-8767	6 1/2	7/8	2 13/16	1 7/16	1	2 1/8	1/4	1/16	3.28
901-8785	8 1/2	1	3 3/16	1 11/16	1 1/8	2 3/8	1/4	1/16	4.66

NOTE: Proof load 2.2 times Safe Working Load. Minimum Ultimate Strength is 6 times the Safe Working Load.

All dimensions approximate and subject to minor changes without notice