



FORGED ALLOY SHACKLES

BOLT TYPE ANCHOR SHACKLES



K-1015

- Safe Working Load is permanently shown on every shackle.
- Alloy bows, Alloy bolts.
- Individually proof tested.

Part No.	Safe Working Load* Tons	Nominal Shackle Size Inches	Inside Length 2140	Inside Width at P'n	DIMENSIONS IN INCHES		Tolerances Plus or Minus		Weight Pounds Each
					Pin Diameter	Outside of Eye			
902-1110	30	1½	5¾	2¾	1⅝	3⅝	¼	⅛	20.80
902-1138	40	1¾	7	2⅞	2	4⅝ ₁₆	¾	⅛	33.91
902-1156	50	2	7¾	3¼	2¼	5	¾	⅛	51.75
902-1174	80	2½	10½	4⅞	2¾	6	¾	¼	101.59
902-1192	110	3	13	5	3¼	6½	¼	¼	178.
902-1218	140	3½	14⅝	5¼	3¾	8	¼	¼	265.
902-1236	175	4	14½	5½	4¼	9	¼	¼	338.

*Proof Load is 2.2 times the Safe Working Load.

Minimum Ultimate Strength is 6 times the Safe Working Load.

All dimensions approximate and subject to minor changes without notice.