



W.J. KEATING LIMITED




K-1016

**ALLOY STEEL BOW SHACKLES
HEAT TREATED
FOR OPTIMUM STRENGTH**

Part No.	Working Load Tonnes	Body		Pin		Jaw		Inside Length		Approx. Weight each
		ins	d mm	ins	D mm	ins	W mm	ins	S mm	
102-1400	150	4	102	4 1/2	115	6 1/2	165	17	432	180 Kg
102-1414	200	4 1/2	115	4 7/8	125	7	178	20	508	240 Kg
102-1450	300	5 1/4	133	5 3/4	146	8	204	24	610	380 Kg
102-1478	400	6	153	6 5/8	168	8 3/4	222	26	661	560 Kg
102-1496	500	7	175	7 1/2	191	9 1/2	242	28	712	800 Kg

Fitted with a special hand grip using a W3 TYPE PIN



**For working loads
up to 500 tonnes**

Recommended Working Load Limit in Tonnes stamped on each Shackle.

*Average Working Load Limit to ultimate Breaking Load is 6 to 1 up to 50 tonnes, 5 to 1 from 62 tonnes and over.

Proof Load equals Twice Working Load Limit up to 50 tonnes. Over this size according to I.L.O. specification.

When ordering use Shackle Code Letter and load with type of pin required.

Test Certificates supplied.

Table dimensions given are subject to normal tolerances.