





SHANK HOOKS



K-1018

- Forged Steel, alloy steel, hi-strength bronze *
- Load Rating stamped on each hook.

NOTE: Proof load is twice safe working load. $\frac{3}{4}$ ton through 50 ton carbon — average straightening load (ultimate load) is five times safe working load. All bronze and alloy hooks — average straightening load (ultimate load) is four times safe working load.



Shank Hook Dimensions with Latch Assembled

Part No. Carbon	Part No. Alloy	Safe Working Load — Tons			DIMENSIONS IN INCHES														Weight Pounds Each
		C*	A	B	A	B	C	D	E	G	H	K	R	L	O	T			
902-4180	902-4607	$\frac{1}{4}$	1	5	59	2.00	.69	2.88	.94	.75	.81	.56	2.28	5.00	.88	.81	.50		
902-4206	902-4625	$\frac{1}{2}$	$1\frac{1}{2}$	6	66	2.25	.78	3.19	1.03	.84	.94	.62	2.53	5.62	.97	.81	.75		
902-4224	902-4643	$1\frac{1}{2}$	2	1.0	72	2.50	.88	3.62	1.06	1.00	1.16	.75	2.89	6.22	1.00	.84	1.00		
902-4242	902-4661	2	3	1.4	88	2.75	1.00	4.09	1.22	1.12	1.31	.84	3.06	6.94	1.12	1.19	1.85		
902-4260	902-4689	3	$4\frac{1}{2}$	2.0	1.16	3.25	1.25	4.94	1.50	1.44	1.62	1.12	3.78	8.47	1.34	1.38	3.85		
902-4288	902-4705	5	7	3.5	1.41	3.75	1.56	6.50	1.88	1.81	2.06	1.38	4.75	10.31	1.69	1.78	7.25		
902-4304	902-4723	$7\frac{1}{2}$	11	5.0	1.69	4.25	1.94	7.56	2.25	2.25	2.62	1.62	5.88	12.38	2.06	2.12	13.00		
902-4322	902-4741	10	15	6.5	1.84	4.50	2.19	8.69	2.50	2.59	2.94	1.94	6.44	13.50	2.25	2.56	17.25		
902-4340	902-4769	15	22	10.0	2.25	5.50	2.62	11.00	3.38	3.00	3.50	2.38	7.94	16.44	3.00	2.88	33.00		
902-4386	902-4803	20	30	13.0	2.75	10.00	3.12	13.62	4.00	3.66	4.62	3.00	9.44	23.09	3.62	3.44	72.00		
902-4402	902-4821	20	30	—	2.75	18.00	3.12	13.62	4.00	3.66	4.62	3.00	9.44	31.09	3.62	3.44	85.50		
902-4420	902-4849	25	37	—	4.00	15.00	3.25	14.06	4.25	4.56	5.00	3.75	11.69	31.25	3.75	3.88	134.00		
902-4448	902-4867	25	37	—	4.00	24.00	3.25	14.06	4.25	4.56	5.00	3.75	11.69	40.25	3.75	3.88	172.00		
902-4466	902-4885	30	45	—	4.00	15.00	3.50	15.44	4.75	5.06	5.50	4.12	13.00	33.06	4.25	4.75	182.00		
902-4464	902-4901	30	45	—	4.00	24.00	3.50	15.44	4.75	5.06	5.50	4.12	13.00	42.06	4.25	4.75	214.00		
902-4509	902-4929	40	60	—	4.50	14.50	4.12	18.50	5.75	6.00	6.50	4.62	15.50	36.00	5.12	5.69	268.00		
902-4545	902-4965	40	60	—	4.50	26.00	4.12	18.50	5.75	6.00	6.50	4.62	15.50	47.50	5.12	5.69	312.00		
902-4563	902-4983	50	75	—	5.00	15.00	4.50	20.62	6.50	6.69	7.25	5.00	19.38	41.06	—	—	390.00		
902-4581	902-5009	50	75	—	5.00	23.00	4.50	20.62	6.50	6.69	7.25	5.00	19.38	49.06	—	—	426.00		
	902-5027	—	100	—	7.00	15.00	7.00	23.12	5.88	6.62	9.88	5.50	18.50	42.12	—	—	610.00		
	902-5045	—	100	—	7.00	21.00	7.00	23.12	5.88	6.62	9.88	5.50	18.50	48.12	—	—	675.00		
	902-5063	—	150	—	7.25	18.00	7.25	24.38	6.00	9.12	10.88	6.00	18.50	45.62	—	—	735.00		
	902-5081	—	200	—	8.00	20.00	8.00	26.69	6.50	10.00	11.81	7.00	20.50	50.50	—	—	1020.00		
	902-5090	—	300	—	9.50	20.00	9.50	30.12	8.00	10.94	12.94	7.25	23.75	54.69	—	—	1390.00		

A — Alloy steel B — Bronze, high strength C — Carbon steel

*Available hot dip galvanized thru 15 tons

*Bronze Hooks made to order.

All dimensions approximate and subject to minor changes without notice.