



W.J. KEATING LIMITED


CHAIN HOOKS

CLEVIS GRAB HOOKS



Forged
Carbon
Steel
Quenched &
Tempered

Forged
Alloy Steel
Quenched &
Tempered



K-1024


Part No. C.S.	Part No. Alloy	Size of Chain	Safe Working Load		DIMENSIONS IN INCHES					Weight Pounds Each
			C.S.	ALLOY	B	E	F	R		
902-7102	902-7249	1/4"	2,800	3,800	1 1/8	1 1/2	3/8	1 1/8	35	
902-7123	902-7267	5/16"	3,300	5,400	1 1/2	1 3/4	7/16	2 1/8	55	
902-7141	902-7285	3/8"	5,400	7,500	1 3/4	1 7/8	7/16	2 1/8	1.00	
902-7169	902-7301	1/2"	7,200	10,000	2 1/8	2 1/8	7/16	2 1/8	1.25	
902-7187	902-7329	5/8"	9,200	12,750	2 3/8	2 3/8	7/16	2 1/8	2.05	
902-7203	902-7347	3/4"	12,750	19,000	2 3/4	2 3/4	7/16	2 1/8	4.25	
902-7221	902-7365	7/8"	16,500	27,000	3 1/8	3 1/8	7/16	2 1/8	5.70	

CLEVIS SLIP HOOKS



Forged
Carbon
Steel
Quenched &
Tempered

Forged
Alloy Steel
Quenched &
Tempered



K-1025

Part No. Carbon	Part No. Alloy	Size of Chain	Safe Working Load* Lbs.		DIMENSIONS IN INCHES				Weight Pounds Each
			Sprocket Application		B	E	F	R	
			C.S.	ALLOY					
902-7383	902-7524	1/4"	1,950	2,750	1 1/8	1 1/2	3/8	2 1/8	50
902-7408	902-7542	5/16"	2,875	4,300	1 1/2	1 3/4	7/16	2 1/8	75
902-7427	902-7560	3/8"	4,000	5,250	1 3/4	1 7/8	7/16	2 1/8	1.13
902-7445	902-7588	1/2"	5,000	7,000	2 1/8	2 1/8	7/16	2 1/8	2.05
902-7463	902-7604	5/8"	6,500	9,000	2 3/8	2 3/8	7/16	2 1/8	2.75
902-7481	902-7622	3/4"	9,250	13,500	2 3/4	2 3/4	7/16	2 1/8	4.75
902-7499	902-7640	7/8"	—	19,250	3 1/8	3 1/8	7/16	2 1/8	11.25


*Ultimate Load is four times the Safe Working Load.

EYE GRAB HOOKS



Forged
Carbon
Steel
Quenched &
Tempered

Forged
Alloy Steel
Quenched &
Tempered



K-1026


Part No. Carbon	Part No. Alloy	Size in Chain	SAFE WORKING LOAD*		DIMENSIONS IN INCHES					Weight Pounds Each
			C.S.	ALLOY	B	E	F	R		
902-6304	902-6364	1/4"	2,600	3,800	1 1/8	1 1/2	3/8	1 1/8	28	
902-6322	902-6401	5/16"	3,900	5,400	1 1/2	1 3/4	7/16	2 1/8	50	
902-6340	902-6429	3/8"	5,400	7,500	1 3/4	1 7/8	7/16	2 1/8	81	
902-6358	902-6446	1/2"	7,200	10,000	2 1/8	2 1/8	7/16	2 1/8	1.25	
902-6376	902-6464	5/8"	9,200	12,750	2 3/8	2 3/8	7/16	2 1/8	1.75	
902-6394	902-6482	3/4"	12,750	19,000	2 3/4	2 3/4	7/16	2 1/8	3.25	
902-6412	902-6501	7/8"	16,500	27,000	3 1/8	3 1/8	7/16	2 1/8	6.00	
902-6430	902-6525	1"	24,000	35,000	3 3/8	3 3/8	7/16	2 1/8	9.17	
902-6448	902-6543	1 1/4"	30,000	45,000	4 1/8	4 1/8	7/16	2 1/8	14.00	

EYE SLIP HOOKS



Forged
Carbon
Steel
Quenched &
Tempered

Forged
Alloy Steel
Quenched &
Tempered



K-1027

Part No Carbon	Part No Alloy	Size of Chain	Safe Working Load* Lbs.		DIMENSIONS IN INCHES			Weight Pounds Each
			Slip Hook Application		B	E	R	
			C.S.	ALLOY				
902-6749	902-6927	1/4"	1,950	2,750	1/2	1 1/16	2 1/32	.40
902-6767	902-6945	5/16"	2,875	4,300	5/8	1 1/16	2 3/32	.70
902-6785	902-6963	3/8"	4,000	5,250	23/32	1 5/16	3 1/16	1.00
902-6801	902-6981	1/2"	5,000	7,000	1 1/8	1 7/8	3 7/8	1.56
902-6829	902-7007	5/8"	6,500	9,000	1 5/8	1 11/16	4 5/16	2.31
902-6847	902-7025	3/4"	9,250	13,500	1 7/8	2	5 1/16	3.78
902-6865	902-7043	7/8"	12,500	19,250	1 3/4	2 1/8	5 3/16	6.25
902-6883	902-7061	1"	17,250	26,000	1 15/16	2 3/8	7 1/16	10.42
902-6909	902-7089	1 1/4"	22,700	34,000	1 13/16	3	8 3/16	15.50

*Ultimate Load is four times the Safe Working Load.

All dimensions approximate and subject to minor changes without notice