



HOOKS • SNAP • CHOKER

K-1054



- FORGED ALLOY STEEL through $\frac{3}{4}$ "
- CAST ALLOY STEEL — $\frac{7}{8}$ " through $1\frac{1}{2}$ "
- Wide throat to take heavy thimbles.

*Ultimate Load is 5 times Safe Working Load.

†When ordering, EYE diameter ("C") should be specified.

SLIDING CHOKER HOOKS Quenched & Tempered

Part No.	Single Part Rope Size	Eight Part Rope Size	Safe Working Load* Pounds	DIMENSIONS IN INCHES				Weight Pounds Each
				A	C	E	L	
902-8042	$\frac{3}{8}$		2,500	$2\frac{1}{16}$	$\frac{5}{8}$	$\frac{5}{8}$	$4\frac{9}{32}$	.75
902-8060	$\frac{1}{2}$	$\frac{1}{8}$	3,300	$2\frac{1}{4}$	$\frac{3}{4}$	$2\frac{5}{32}$	$4\frac{31}{32}$	1.25
902-8088	$\frac{5}{16}$	$\frac{3}{16}$	5,000	$3\frac{1}{16}$	$\frac{3}{4}$ or 1	$1\frac{5}{16}$	$6\frac{3}{8}$	3.10
902-8122	$\frac{3}{4}$	$\frac{1}{4}$	8,000	$3\frac{3}{8}$	1 or $1\frac{7}{16}$	$1\frac{5}{32}$	$7\frac{21}{32}$	5.00
902-8168	$\frac{7}{8}$ - 1	$\frac{3}{8}$	15,000	$4\frac{1}{2}$	$1\frac{1}{4}$ or 2	$1\frac{5}{8}$	$9\frac{1}{2}$	16.25
902-8202	$1\frac{1}{8}$ - $1\frac{1}{4}$	$\frac{7}{16}$	23,000	$5\frac{5}{8}$	$2\frac{5}{16}$	$1\frac{3}{4}$	$11\frac{5}{8}$	28.25
902-8220	$1\frac{3}{8}$ - $1\frac{1}{2}$	$\frac{1}{2}$ - $\frac{9}{16}$	30,000	7	$2\frac{13}{16}$	$2\frac{3}{16}$	$14\frac{1}{2}$	67.50

K-1055



- Pressed steel latches and stainless steel springs, bolts and nuts.
- Safe Working Loads shown are based on Ultimate Load that is 4 times the Safe Working Load.

SNAP HOOKS Forged Steel, Quenched & Tempered Galvanized

Part No.	Hook Size Inches	Safe Working Load Pounds	Inside Diam. of Eye Inches	Throat Opening Inches	Length Overall Inches	Weight Pounds Per 100
902-3056	$\frac{7}{16}$	750	$\frac{3}{4}$	$\frac{3}{4}$	$3\frac{15}{16}$	24.00
902-3074	$\frac{9}{16}$	1,000	$1\frac{1}{8}$	$1\frac{3}{16}$	$4\frac{3}{4}$	50.00

SWING LINKS

FORGED STEEL

- Forged steel half links connected by a bronze rivet, for the quick connecting of chain links.
- The link, and interlocking lugs, remain firmly joined while under tension.
- The link is easily removed when the tension is relaxed.

K-1056



Part No.	Size Inches	DIMENSIONS IN INCHES			Weight Pounds Per 100
		Width	Length	I.D. Eye	
901-4397	$\frac{1}{4}$	$\frac{7}{8}$	$1\frac{7}{8}$	$\frac{3}{16}$	8.5
901-4413	$\frac{5}{16}$	1	$2\frac{1}{8}$	$\frac{3}{16}$	12
901-4431	$\frac{3}{8}$	$1\frac{5}{16}$	$2\frac{9}{16}$	$\frac{9}{16}$	20.5
901-4459	$\frac{1}{2}$	$1\frac{5}{8}$	$3\frac{9}{16}$	$\frac{5}{8}$	43
901-4477	$\frac{5}{8}$	$2\frac{1}{16}$	$4\frac{3}{16}$	$1\frac{3}{16}$	92
901-4495	$\frac{3}{4}$	$2\frac{9}{16}$	$4\frac{7}{8}$	$1\frac{1}{16}$	155
901-4510	1	$3\frac{1}{4}$	$6\frac{1}{2}$	$1\frac{1}{4}$	345