



Drop Forged, Galvanized Hooks

Specifications and Stock Numbers, 4181



Round,
Loose
Hook.

K-3010

Size Inches	Stock Number	Dimensions in Inches			Weight in Pounds	Working Load Limit*, Pounds
		Length	I.D. of Eye	Throat Opening		
1/2	389-0835	3 7/16	7/8	3/4	5 1/16	500
5/8	389-1035	4 3/8	1 1/16	1 5/16	5 5/8	700
3/4	389-1235	4 7/8	1 3/16	1 1/16	7 7/8	1,200
7/8	389-1435	5 1/2	1 1/4	1 1/4	1 5/16	1,500
1	389-1635	6 1/2	1 7/16	1 5/16	2 1/16	1,800
1 1/8	389-1835	7	1 1/2	1 7/16	2 3/4	2,200
1 1/4	389-2035	7 3/16	1 5/8	1 5/8	4	2,900
1 3/8	389-2235	8 1/2	1 13/16	1 13/16	5 5/16	3,300
1 1/2	389-2435	9 1/4	1 15/16	2	6	3,700

Specifications and Stock Numbers, 4184




Bosloc
Safety Hook.

K-3011

Hook Number	Stock Number	Dimensions in Inches			Weight in Pounds	Working Load Limit*, Tons
		Length	Swivel Size	Throat Opening		
2	389-6235	5 7/16	3/8	1	1	3/4
3	389-6335	6 1/32	7/16	1	1 1/2	1 1/2
4	389-6435	7 1/8	1/2	1	2 1/4	2
5	389-6535	7 9/16	1/2	1 1/8	2 3/4	3
6	389-6635	8 3/4	9/8	1 5/16	3 1/2	4
7	389-6735	9 5/32	5/8	1 3/8	5	4 1/2

HANDY LATCH HOOK

An ideal hook for single line crane service—fast, simple, safe. The hook tender can position the hook and operate the latch with one hand. The spring loaded safety latch closes automatically on trigger release. These cast alloy steel hooks are heat treated, 100% Magnaflex inspected, and proof tested—to insure utmost reliability.



CAPACITY TONS	LINE SIZE	A	B	C	D	E	F	G	M	N	P	WEIGHT
5	5/8 - 3/4	1-1/32	1	1 3/8	12 1/4	2 1/4	15 7/8	7	2	2 3/4	1 1/4	22
10	7/8 - 1	1-9/32	1 1/4	1 5/8	13	3	17 3/4	8 1/2	2 1/2	3 1/2	1 1/2	35
15	1 1/8 - 1 1/4	1-17/32	1 1/2	1 7/8	14 3/4	3 3/4	20 1/4	10 1/4	3	4	2	49

K-3012