



WIRE ROPE THIMBLES

STANDARD WIRE ROPE THIMBLES

Hot Dip Galvanized Steel

Part No.	For Rope Diam. Inches	DIMENSIONS IN INCHES						Weight Pounds Per 100
		Overall Length	Overall Width	Length Inside	Width Inside	Inside Width of Score	Max. Pin Diam.	
903-7256	1/8	1 15/16	1 1/8	1 1/8	1 1/8	5/32	5/8	1.50
903-7274	3/16	1 15/16	1 1/8	1 1/8	1 1/8	7/32	5/8	2.50
903-7292	1/4	1 15/16	1 1/8	1 1/8	1 1/8	5/32	5/8	3.75
903-7318	5/16	2 1/8	1 1/4	1 1/2	1 1/8	3/8	3/4	4.00
903-7336	3/8	2 3/8	1 15/16	1 5/8	1 1/8	7/16	3/4	6.25
903-7354	1/2	2 3/4	1 3/4	1 7/8	1 1/8	5/16	1 1/8	13.12
903-7372	5/8	3 1/2	2 3/8	2 1/4	1 3/8	1 1/16	1 1/2	36.00
903-7390	3/4	3 3/4	2 11/16	2 1/2	1 5/8	1 1/16	1 1/2	50.00
903-7418	7/8	5	3 1/2	3 1/2	1 7/8	1 1/16	1 3/4	85.00
903-7434	1	5 11/16	3 3/4	4 1/4	2 1/2	1 1/16	2 3/8	100.00
903-7452	1 1/8 - 1 1/4	6 1/4	4 1/8	4 1/2	2 3/4	1 1/16	2 3/8	175.00
903-7470	1 1/2	7 1/2	5 3/8	5	3 1/4	1 1/16	3 1/8	325.00
903-7498	1 3/4	10 3/4	7 1/4	7 1/4	4 1/4	1 7/8	4 1/8	575.00
903-7513	2	10 3/4	7 1/4	7 1/4	4 1/4	2 1/8	4 1/8	600.00

K-1028



STANDARD

Recommended for light service. Meets Federal Specification FF-T-276b Type II.

EXTRA HEAVY WIRE ROPE THIMBLES

Hot Dip Galvanized and Stainless Steel

Part No. Galvanized	Part No. Stainless Steel	For Rope Diam. Inches	DIMENSIONS IN INCHES						Weight Pounds Per 100
			Overall Length	Overall Width	Length Inside	Width Inside	Overall Thickness	Max. Pin Diam.	
903-7639	903-7960	1/4	2 1/8	1 1/2	1 1/8	7/8	1 1/32	1 1/16	6.25
903-7657	903-7988	5/16	2 1/2	1 13/16	1 7/8	1 1/16	1/2	1 1/8	12.50
903-7675	903-8004	3/8	2 7/8	2 1/8	2 1/8	1 1/8	2 1/32	1 1/8	25.00
903-7693	—	7/16	3 1/4	2 3/8	2 3/8	1 1/4	3/4	1 3/8	33.00
903-7719	903-8022	1/2	3 3/8	2 3/4	2 3/4	1 1/2	27/32	1 7/8	50.00
903-7737	—	5/8	3 5/8	2 11/16	2 3/4	1 1/2	29/32	1 7/8	51.00
903-7755	903-8040	3/4	4 1/8	3 1/8	3 1/4	1 3/4	1	1 5/8	75.00
903-7773	903-8068	3/4	5	3 13/16	3 3/4	2	1 1/4	1 7/8	145.00
903-7791	—	7/8	5 1/2	4 1/4	4 1/4	2 1/4	1 3/8	2 1/8	175.00
903-7817	—	1	6 1/8	4 15/16	4 1/2	2 1/2	1 5/8	2 3/8	275.00
903-7835	—	1 1/8 - 1 1/4	7	5 3/8	5 1/8	2 3/8	1 7/8	2 3/4	400.00
903-7853	—	1 1/8 - 1 3/8	9 1/16	6 13/16	6 1/2	3 1/2	2 1/4	3 1/4	817.00
903-7871	—	1 3/8 - 1 1/2	9	7 1/8	6 1/4	3 1/2	2 3/8	3 3/8	1,175.00
903-7899	—	1 5/8	11 1/4	8 1/8	8	4	2 3/4	3 3/8	1,700.00
903-7915	—	1 3/4	12 1/8	8 1/2	8	4 1/2	2 3/8	4 1/8	1,775.00
903-7933	—	1 7/8 - 2	15 1/8	10 3/8	12	6	3 1/8	5 3/8	2,500.00
903-7951	—	2 1/4	17 1/8	11 7/8	14	7	3 1/8	6 3/8	3,925.00

(STAINLESS STEEL)

K-1029



K-1030

EXTRA HEAVY

A rugged rope thimble recommended for heavy duty service. Thimbles meet Federal Specification FF-T-276b Type III.

SOLID WIRE ROPE THIMBLES

Part No.	For Rope Diam. Inches	DIMENSIONS IN INCHES				Weight Pounds Each
		Overall Length	Overall Width	Thickness	Maximum Pin Diam.	
903-7121	1/2	2 1/8	2 1/8	7/8	1	50
903-7149	5/8	4 11/16	3 3/8	1 1/8	1 1/8	2.25
903-7167	3/4	4 11/16	3 3/8	1 3/8	1 3/8	2.25
903-7185	7/8	6 1/16	4 1/2	1 3/8	1 5/8	6.00
903-7201	1	6 1/16	4 1/2	1 3/8	2	5.12
903-7229	1 1/8	7 1/4	5 3/8	2 1/8	2 1/4	10.00
903-7247	1 1/2 - 1 3/8	7 1/4	5 3/8	2 1/8	2 1/2	10.25

K-1034



SOLID

Fits open wire rope socket, boom pendant clevis.

All dimensions approximate and subject to minor changes without notice.