



W.J. KEATING LIMITED

LIFTING EYES • EYE NUTS • PAD EYES

LIFTING EYES

Forged Steel


K-1044



Large eye dimensions to accommodate a hook for lifting or pulling. The Eye and Shank are forged in one piece.

Part No.	Size No.	DIMENSIONS IN INCHES										Weight Pounds Each	Safe Working Load When Threaded - Pounds*
		A	C	D	E	F	G	H	L	S	T		
909-0269	1	1 1/4	3/4	1 1/16	1 1/32	1/2	3/8	5/16	1 1/16	1/4	2 3/8	.10	850
909-0287	2	1 5/8	1	1 1/4	3/4	9/16	1/2	3/8	1 5/16	3/16	3	.20	1,250
909-0303	3	2	1 1/4	1 1/2	1	1 1/16	5/8	1/2	1 1/4	3/8	3 3/4	.25	2,250
909-0321	4	2 1/2	1 1/2	2	1 3/16	1	1 1/16	5/8	1 1/2	1/2	4 1 1/16	.79	3,600
909-0349	5	3	1 3/4	2 3/8	1 3/8	1 1/8	7/8	3/4	1 3/8	5/8	5 5/8	1.25	5,200
909-0367	6	3 1/2	2	2 5/8	1 5/8	1 5/16	1 5/16	7/8	2	3/4	6 5/16	2.25	7,200
909-0385	7	4	2 1/4	3 1/16	1 7/8	1 9/16	1 1/16	1	2 1/16	3/4	7 1/16	3.25	10,000
909-0401	8	4 1/2	2 1/2	3 1/2	1 11/16	1 7/8	1 1/4	1 1/8	2 1/2	1	8 1/4	4.70	12,500
909-0429	9	5	2 3/4	3 3/4	2	2	1 3/8	1 1/4	2 3/4	1 1/8	9	6.25	15,200
909-0410	10	5 5/8	3 1/8	4	2 3/8	2 3/8	1 1/2	1 3/8	2 13/16	1 1/4	9 11/16	9.33	18,000

*Ultimate Load is five times the Safe Working Load
*Based on thread size equal to specified shank diameter



K-1045



EYE NUTS
EYE NUTS (BLANK)

EYE NUTS Forged Steel, Hot Dip Galvanized, Threaded, Quenched and Tempered

Part No.	Size No.	Std. Tap M	DIMENSIONS IN INCHES							Max. Tap Size Possible	Weight Pounds Each	Safe Working Load - Pounds
			A	C	D	E	F	S	T			
909-0438	1	1/4	1 1/4	3/4	1 1/16	2 1/32	1/2	1/4	1 1/16	3/8	.10	520
909-0456	1A	5/16	1 1/4	3/4	1 1/16	2 1/32	1/2	1/4	1 1/16	3/8	.10	850
909-0474	2	3/8	1 5/8	1	1 1/4	3/4	9/16	5/16	2 1/16	7/16	.18	1,250
909-0492	3	7/16	2	1 1/4	1 1/2	1	1 1/16	3/8	2 1/2	1/2	.29	1,700
909-0517	3A	1/2	2	1 1/4	1 1/2	1	1 1/16	3/8	2 1/2		.28	2,250
909-0535	4	5/8	2 1/2	1 1/2	2	1 3/16	1	1/2	3 3/16	3/4	.58	3,600
909-0553	5	3/4	3	1 3/4	2 3/8	1 3/8	1 1/8	3/4	3 7/8	7/8	1.00	5,200
909-0571	6	7/8	3 1/2	2	2 3/8	1 5/8	1 5/16	3/4	4 5/16	1	1.70	7,200
909-0599	7	1	4	2 1/4	3 1/8	1 7/8	1 9/16	7/8	5	1 1/4	2.75	10,000
909-0615	7A	1 1/8	4	2 1/4	3 1/16	1 7/8	1 9/16	7/8	5	1 1/4	2.75	12,300
909-0633	8	1 1/4	4 1/2	2 1/2	3 1/2	1 11/16	1 7/8	1	5 3/4	1 1/2	3.85	15,500
909-0651	9	1 3/8	5	2 3/4	3 3/4	2	2	1 1/8	6 1/4	1 1/2	5.00	18,500
909-0679	10	1 1/2	5 5/8	3 3/8	4	2 3/8	2 1/4	1 1/4	6 3/4	1 3/4	6.70	22,500
909-0697	11	2	7	4	6 1/4	4	3 3/8	1 1/2	10	2 3/4	17.00	40,000
909-0713	11A	2 1/2	7	4	6 1/4	4	3 3/8	1 1/2	10	2 3/4	15.50	45,200

*Ultimate Load is five times the Safe Working Load.

ORDER EYE NUTS BY SIZE NUMBER

All dimensions approximate and subject to minor changes without notice.

PAD EYES Forged Steel

Forged from 1035 carbon steel with excellent qualities for welding, widely used on farm machinery, trucks, steel-hulled marine vessels, and material handling equipment.

Part No.	Size No.	Inside Diam. of Eye Inches	Outside Diam. of Eye Inches	Diam. of Shoulder Inches	Overall Height Inches	Weight Pounds Per 100
909-0722	0	1/4	5/8	5/8	3/4	2.77
909-0740	1	3/8	7/8	7/8	1 1/32	6.94
909-0768	1 1/2	5/8	1 1/8	1	1 5/16	10.25
909-0786	2	3/4	1 1/2	1 1/16	1 5/8	17.25
909-0802	4	1	2 1/8	1 7/16	2 11/32	50.00
909-0820	5	1 1/4	2 5/8	1 3/4	2 3/4	82.50

K-1046

