



FORGED EYE BOLTS



K-1061

REGULAR NUT

Hot Dip Galvanized, Forged Steel, $\frac{1}{4}$ through $\frac{1}{2}$ " Sizes
Normalized, Larger Sizes Quenched and Tempered

Part No.	Shank Diam. and Length Inches	Length of Thread Inches	Eye Dim.		Safe Working Load* Pounds	Weight Pounds Per 100
			I.D. Inches	O.D. Inches		
904-3230	$\frac{1}{4}$ x 2	1 $\frac{1}{2}$	$\frac{1}{2}$	1	500	6.00
904-3258	$\frac{1}{4}$ x 4	2 $\frac{1}{2}$	$\frac{1}{2}$	1	500	12.50
904-3276	$\frac{5}{16}$ x 2 $\frac{1}{2}$	1 $\frac{1}{2}$	$\frac{5}{8}$	1 $\frac{1}{4}$	800	18.75
904-3294	$\frac{5}{16}$ x 4 $\frac{1}{2}$	2 $\frac{1}{2}$	$\frac{5}{8}$	1 $\frac{1}{4}$	800	25.00
904-3310	$\frac{3}{8}$ x 2 $\frac{1}{2}$	1 $\frac{1}{2}$	$\frac{3}{4}$	1 $\frac{1}{2}$	1,200	31.25
904-3338	$\frac{3}{8}$ x 4 $\frac{1}{2}$	2 $\frac{1}{2}$	$\frac{3}{4}$	1 $\frac{1}{2}$	1,200	37.50
904-3356	$\frac{3}{8}$ x 6	2 $\frac{1}{2}$	$\frac{3}{4}$	1 $\frac{1}{2}$	1,200	43.75
904-3374	$\frac{1}{2}$ x 3 $\frac{1}{4}$	1 $\frac{1}{2}$	1	2	2,200	50.00
904-3392	$\frac{1}{2}$ x 6	3	1	2	2,200	62.50
904-3418	$\frac{1}{2}$ x 8	3	1	2	2,200	75.00
904-3436	$\frac{1}{2}$ x 10	3	1	2	2,200	88.00
904-3454	$\frac{1}{2}$ x 12	3	1	2	2,200	100.00
904-3472	$\frac{5}{8}$ x 4	2	1 $\frac{1}{4}$	2 $\frac{1}{2}$	3,500	101.25
904-3490	$\frac{5}{8}$ x 6	3	1 $\frac{1}{4}$	2 $\frac{1}{2}$	3,500	125.00
904-3515	$\frac{5}{8}$ x 8	3	1 $\frac{1}{4}$	2 $\frac{1}{2}$	3,500	150.00
904-3533	$\frac{5}{8}$ x 10	3	1 $\frac{1}{4}$	2 $\frac{1}{2}$	3,500	162.50
904-3551	$\frac{5}{8}$ x 12	4	1 $\frac{1}{4}$	2 $\frac{1}{2}$	3,500	175.00
904-3579	$\frac{3}{4}$ x 4 $\frac{1}{2}$	2	1 $\frac{1}{2}$	3	5,200	156.00
904-3597	$\frac{3}{4}$ x 6	3	1 $\frac{1}{2}$	3	5,200	168.00
904-3613	$\frac{3}{4}$ x 8	3	1 $\frac{1}{2}$	3	5,200	200.00
904-3631	$\frac{3}{4}$ x 10	3	1 $\frac{1}{2}$	3	5,200	238.00
904-3659	$\frac{3}{4}$ x 12	4	1 $\frac{1}{2}$	3	5,200	252.00
904-3677	$\frac{3}{4}$ x 15	5	1 $\frac{1}{2}$	3	5,200	300.00
904-3695	$\frac{7}{8}$ x 5	2 $\frac{1}{2}$	1 $\frac{3}{4}$	3 $\frac{1}{2}$	7,200	215.00
904-3711	$\frac{7}{8}$ x 8	4	1 $\frac{3}{4}$	3 $\frac{1}{2}$	7,200	325.00
904-3739	$\frac{7}{8}$ x 12	4	1 $\frac{3}{4}$	3 $\frac{1}{2}$	7,200	400.00
904-3757	1 x 6	3	2	4	10,000	425.00
904-3775	1 x 9	4	2	4	10,000	452.00
904-3793	1 x 12	4	2	4	10,000	550.00
904-3819	1 x 18	7	2	4	10,000	650.00
904-3837	1 $\frac{1}{4}$ x 8	4	2 $\frac{1}{2}$	5	15,200	750.00
904-3855	1 $\frac{1}{4}$ x 12	4	2 $\frac{1}{2}$	5	15,200	900.00
904-3873	1 $\frac{1}{4}$ x 20	6	2 $\frac{1}{2}$	5	15,200	1,150.00

*Ultimate Load is five times the Safe Working Load

All eye bolts on this page are normalized up to and including $\frac{3}{8}$ inch sizes. Larger sizes are quenched and tempered.



K-1062

SHOULDER NUT

Hot Dip Galvanized, Forged Steel,
Quenched and Tempered

Part No.	Shank Diam. and Length Inches	Length of Thread Inches	Eye Dim.		Safe Working Load* Pounds	Weight Pounds Per 100
			I.D. Inches	O.D. Inches		
904-5014	$\frac{1}{4}$ x 2	1 $\frac{1}{2}$	$\frac{1}{2}$	$\frac{7}{8}$	500	3.75
904-5032	$\frac{1}{4}$ x 4	2 $\frac{1}{2}$	$\frac{1}{2}$	$\frac{7}{8}$	500	6.25
904-5050	$\frac{5}{16}$ x 2 $\frac{1}{2}$	1 $\frac{1}{2}$	$\frac{5}{8}$	1 $\frac{1}{4}$	800	12.50
904-5078	$\frac{5}{16}$ x 4 $\frac{1}{2}$	2 $\frac{1}{2}$	$\frac{5}{8}$	1 $\frac{1}{4}$	800	18.75
904-5096	$\frac{3}{8}$ x 2 $\frac{1}{2}$	1 $\frac{1}{2}$	$\frac{3}{4}$	1 $\frac{1}{2}$	1,200	19.00
904-5112	$\frac{3}{8}$ x 4 $\frac{1}{2}$	2 $\frac{1}{2}$	$\frac{3}{4}$	1 $\frac{1}{2}$	1,200	31.58
904-5130	$\frac{1}{2}$ x 3 $\frac{1}{4}$	1 $\frac{1}{2}$	1	1 $\frac{3}{4}$	2,200	37.50
904-5158	$\frac{1}{2}$ x 6	3	1	1 $\frac{3}{4}$	2,200	66.25
904-5176	$\frac{5}{8}$ x 4	2	1 $\frac{1}{4}$	2 $\frac{1}{4}$	3,500	75.00
904-5194	$\frac{5}{8}$ x 6	3	1 $\frac{1}{4}$	2 $\frac{1}{4}$	3,500	100.25
904-5210	$\frac{3}{4}$ x 4 $\frac{1}{2}$	2	1 $\frac{1}{2}$	2 $\frac{3}{4}$	5,200	125.00
904-5238	$\frac{3}{4}$ x 6	3	1 $\frac{1}{2}$	2 $\frac{3}{4}$	5,200	150.00
904-5256	$\frac{3}{4}$ x 5	2 $\frac{1}{2}$	1 $\frac{3}{4}$	3 $\frac{1}{4}$	7,200	225.00
904-5274	$\frac{1}{2}$ x 8	4	1 $\frac{3}{4}$	3 $\frac{1}{4}$	7,200	275.00
904-5292	1 x 6	3	2	3 $\frac{1}{4}$	10,000	375.00
904-5318	1 x 9	4	2	3 $\frac{1}{4}$	10,000	425.00
904-5336	1 $\frac{1}{2}$ x 6	4	2 $\frac{1}{2}$	4 $\frac{1}{2}$	15,200	650.00
904-5354	1 $\frac{1}{2}$ x 12	4	2 $\frac{1}{2}$	4 $\frac{1}{2}$	15,200	775.00
904-5372	1 $\frac{1}{2}$ x 15	6	3	5 $\frac{1}{2}$	21,400	1,425.00

All bolts hot dip galvanized after threading. Hex nuts are American Standard Heavy, hot dip galvanized.

*Ultimate Load is five times the Safe Working Load



K-1063

SCREW EYE BOLTS

Hot Dip Galvanized, Forged Steel,
Quenched and Tempered

Part No.	Shank Diam. and Length Inches	EYE DIM.		Weight Pounds Per 100
		I.D. In.	O.D. In.	
904-6111	$\frac{1}{4}$ x 2	$\frac{1}{2}$	$\frac{7}{8}$	4.25
904-6139	$\frac{5}{16}$ x 2 $\frac{1}{2}$	$\frac{5}{8}$	1 $\frac{1}{4}$	6.25
904-6157	$\frac{3}{8}$ x 2 $\frac{1}{2}$	$\frac{3}{4}$	1 $\frac{3}{4}$	18.75
904-6175	$\frac{1}{2}$ x 3 $\frac{1}{4}$	1	1 $\frac{3}{4}$	37.50
904-6193	$\frac{5}{8}$ x 4	1 $\frac{1}{4}$	2 $\frac{1}{4}$	68.75
904-6219	$\frac{3}{4}$ x 4 $\frac{1}{2}$	1 $\frac{1}{2}$	2 $\frac{3}{4}$	117.50