


# DOORS, HATCHES, MANHOLES


- Fabricated Steel, Aluminum or Stainless
  Steel
- Commercial, A.B.S., Custom



K-3102 - 6 DOG WATERTIGHT DOOR




K-3208 - OVAL DROP BOLT HATCH



K-3201 -WATERTIGHT HATCH




K-3202 - QUICK ACTING HATCH



K-3300 BOLTED PLATE MANHOLE




# WEATHERTIGHT DOORS




# K-20000 - WEATHERTIGHT INSULATED DOORS

- Fabricated in Stainless Steel, Aluminum and Steel
- •2 Dog Positive Locking Adjustable
- Neoprene Gasket
- Hardware Stainless Steel
- Also available without Weathering Dogs.






# **WINDOWS**



#### K-3325-FIXED WINDOW


The type K-325-F matches in appearance the K-322-C and K-325 and is used in conjunction with them or as a separate unit. Made of extruded bronze, aluminum, or stainless steel. Windows can be made to suit curved bulkhead, with square or round corners. Windows may be bevelled to suit sheer or camber.

- Watertight
- Flanged Frame
- Glass 1/4" Heat Treated to 1" Thermopane
- Available to suit custom shapes



### K-3325 WINDOW CRANK OPERATED VERTICALLY SLIDING

- Aluminum, Bronze or Stainless Steel
- Weathertight
- Flanged Frame
- Stainless Steel Drain Pan



### **K-3322 WINDOW**

**Counter Balanced Vertically Sliding** 

- Aluminum, Bronze or Stainless Steel
- Weathertight
- Flanged Frame
- Stainless Steel Drain Pan




## **WINDOWS**



K-3110-SIDE HINGED

Type K-1100 side hinge window designed for installation in Deckhouse, Bridge Fronts and other locations where a heavy-duty watertight window is required.




- Side or Top Hinge
- Watertight
- Adjustable Hinges
- Screw Type Weathering Dogs
- Standard Size 18" x 24" Clear Opening
- Matching Fixed K-1100F Available
- Bolt-on or Weld-in Main Frame Available
- Aluminum, Bronze or Stainless Steel



REFLECTION PROOF WHEELHOUSE FRONT WINDOW



- Available in Single-Double-Triple Panels Fixed or Hinged
- Weathertight
- Frames Aluminum, Steel, Bronze or Stainless Steel




#### **K-3015 WINDOW**

- Top Sash Sliding Down Bottom Sash Fixed
- Weathertight
- Flanged Frame
- Aluminum, Bronze or Stainless Steel




# **WINDOWS**



#### K-3325-FIXED WINDOW


The type K-325-F matches in appearance the K-322-C and K-325 and is used in conjunction with them or as a separate unit. Made of extruded bronze, aluminum, or stainless steel. Windows can be made to suit curved bulkhead, with square or round corners. Windows may be bevelled to suit sheer or camber.

- Watertight
- Flanged Frame
- Glass 1/4" Heat Treated to 1" Thermopane
- Available to suit custom shapes



### K-3325 WINDOW CRANK OPERATED VERTICALLY SLIDING

- Aluminum, Bronze or Stainless Steel
- Weathertight
- Flanged Frame
- Stainless Steel Drain Pan




#### **K-3322 WINDOW**

**Counter Balanced Vertically Sliding** 

- Aluminum, Bronze or Stainless Steel
- Weathertight
- Flanged Frame
- Stainless Steel Drain Pan




# **WINDOWS**




K-3110-SIDE HINGED


Type K-1100 side hinge window designed for installation in Deckhouse, Bridge Fronts and other locations where a heavy-duty watertight window is required.




- Side or Top Hinge
- Watertight
- Adjustable Hinges
- Screw Type Weathering Dogs
- Standard Size 18" x 24" Clear Opening
  Matching Fixed K-1100F Available
- Bolt-on or Weld-in Main Frame Available
- Aluminum, Bronze or Stainless Steel



**REFLECTION PROOF** WHEELHOUSE FRONT WINDOW



- Available in Single-Double-Triple Panels Fixed or Hinged
- Weathertight
- Frames Aluminum, Steel, Bronze or Stainless Steel



#### K-3015 WINDOW

- Top Sash Sliding Down Bottom Sash Fixed
- Weathertight
- Flanged Frame
- · Aluminum, Bronze or Stainless Steel




### **WINDOWS**

#### **DEADLIGHT COVERS**

all windows can be supplied with either outboard or inboard deadlight covers.


#### Types Available:

Hinged Vertically Sliding Horizontally Sliding Non-tight Watertight




#### **K-3522 WINDOW**

- Spring Balanced
- Watertight (Four Dogs)
- Spigoted Frame
- Stainless Steel Drain Pan



#### K-3222 WINDOW

- Spring Balanced
- Weathertight
- Spigoted Frame
- Stainless Steel Drain Pan



#### **K-3225 WINDOW**

Crank Operated
Weathertight
bigoted Frame
ainless Steel Drain Pan



# K-3225 WINDOW WITH COVER

- Crank Operated
- Weathertight
- Spigoted Frame
- Stainless Steel Drain Pan
- Sliding Steel Cover




#### **K-3525 WINDOW**

- Crank Operated
- Watertight (Four Dogs)
- Spigoted Frame
- Stainless Steel Pan





## **WINDOWS**



# K-3100, K-3101, K-3102 WINDOWS HORIZONTALLY SLIDING


- Aluminum Standard Design
- Custom Fabricated in Bronze or Stainless Steel
- Weathertight
- Single or Double Sliding
- Flange Frame
- Custom Shapes Available





#### K-3130-TOP HINGED WINDSHIELD

- · Single or Double Panel
- Aluminum, Bronze or Stainless Steel
- Weathertight
- Flanged Frame





# WINDOW DEFOGGING & DEFROSTING

#### K-3040

# DEICING AND DEFOGGING ELECTRICALLY HEATED WINDOW

Installed on new commercial, Navy, Coast Guard vessels, as well as ships undergoing conversion. Kearfott Heated Windows are used year round under wide range of climate, weather and temperature conditions. The windows are completely assembled and ready for installation.

Electrical energy is supplied to conducting film through bus bars located at opposite edges of glass. Sufficient thermal energy is provided to maintain ice-free, frost-free, fog-free window. Heating is controlled by specially designed sensor controller that monitors the window temperature.


Voltage - 115 - 220 - 440 AC Wattage - 75 to 350 Watts/sq. ft. Mil. Spec. MIL-W-18445





#### **HINGED AND FIXED PORTS**

- Bolt-on or Weld-in
- Sizes: 6" to 24"
- Covers and Insect Screens Available



#### K-3042 CLEAR VIEW SCREEN

- 12" or 14" Dia.
- Double Glazed
- Built-in Heater
- Solid Bronze Construction
- For Mounting in Glass Panel 3/8" Min. to 3/4" Max.



### WINDOW WIPERS


Kearfott PENDULUM Window and Airport Wiper is designed with the sole aim of producing a rugged and simple device to resist the severe conditions inherent in marine operations. All parts are made to withstand corrosion. Mounting arrangements are flexible. The motor housing can be located outboard to the window or airport on any side or can be placed inside the bulkhead with the drive shaft extending through a packing gland.

The unit is powered by a 1/25 h.p. 115 volt AC/DC motor. Also available are 12, 24, and 32 volt DC motors. For operation on 220 volts a fixed resistance unit in enclosure is supplied.


The standard accessories include a combination rheostat speed control and "off" switch in a totally-enclosed case. Maximum arm length 20". Rubber blade length available from 8" to 20".


Various wiper arm arrangements can be furnished including single, dual arms and parallel blade motion.


For operation under severe icing conditions, heated arms on inside mounted wipers and pivot heaters on outside mounted wipers are available.



K-3039







#### **GENERAL ORDERING DATA**

FRAMES - Aluminum - Bronze - Stainless Steel

SIZE — Dimensions of cut in ships bulkhead

**SHAPE** - Rectangular, Parallelogram, or Special Shape Curved or Flat Bulkhead, Camber or Sheer

GLASS - Tempered, Laminated, Deicing Glass, Wire Glass, Lexan, Multiplated Armor Glass or Thermopane

GLASS COLOR - Clear - Tinted (Solar Bronze - Solar Gray)

GLASS THICKNESS - 1/4" - 3/8" - 1/2" - 3/4" or Thermopane - 3/4" or 1"




# **WINDOWS AND PORTLIGHTS**

FULL-VIEW INSIDE TYPE PORT LIGHT — HEAVY TYPE

K-3044

Cast Bronze or Aluminum
Plain, Polished or Chrome



C	Dia. Opening	Dia. Clear Glass	Thickness Glass	Dia. Flange	No. Dog Bolts
	4"	4"	3/8"	6-1/2"	1
	5"	5"	3/8"	8"	1
	6"	6"	3/8"	9"	2
	7"	7"	1/2"	10"	1
	8"	8"	1/2"	11-1/2"	2
3	9"	9"	1/2"	13"	2
	10"	10"	1/2"	14-1/4"	2

- 1. 3 or 4 dogs.
- 2. Hinged or fixed light.
- 3. With or without deadlight cover.
- 4. Steel or brass frame.
- 5. Staggered bolting for wood hull.


#### PLAIN CAST BRONZE OR ALUMINUM



K-3043
OUTSIDE TYPE FIXED LIGHT
Cast Bronze or Aluminum

	iii aiii			
Dia.	Plain or Chrome			
Clear	Dia.	Glass		
Glass	Flanged	Thickness		
4''	65/8''	3/8''		
5''	75/8''	3/8''		
6''	8¾''	3/8''		
7''	93/4''	3/8''		
8''	111/4"	1/2''		
9''	121/4''	1/2''		
10"	131/8''	<sup>1</sup> / <sub>2</sub> ''		

Inside fixed lights available in sizes 6, 7, 8, and 10 inch diameter.




NAVAL PATTERN HEAVY DUTY PORTLIGHT

Naval brass or aluminum

### **DECK COVERS**

Safe, single action BRONZE Deck Cover for tank-cleaning openings




- WEIGHT: 31 lbs. RAPID-SINGLE ACTION TO OPEN OR CLOSE WITH SPEED WRENCH.
  - FLAT, WITH NO PROJECTIONS, PROVIDING MAXIMUM SAFETY.
  - . INSTALLED IN SECONDS.
  - . REPLACEABLE O-RING SEAL.
- . ELIMINATES COSTLY REPLACEMENTS OF STUDS, NUTS AND WASHERS.
- THIS STRONG, RIGID ASSEMBLY MEETS REQUIREMENTS OF AMERICAN BUREAU OF SHIPPING AND LLOYDS REGISTER OF SHIPPING.

### SUITABLE FOR NEW CONSTRUCTION AND CONVERSION


FITS STANDARD 121/2" DECK OPENING WITH ANY DECK THICKNESS UP TO 3"

MATERIAL - NON-SPARKING BRONZE






# **WATERTIGHT DOOR ACCESSORIES**



Specify Type Below: Right Hand, Left Hand or Neutral. Shaft Diameter 'A', Shaft Length 'B'.



K-3063 Left, Right or Neutral



K-3065 Neutral only.



K-3064 Left, Right or Neutral



K-3066 Left, Right or Neutral



K-3067 Neutral only.



K-3068 Neutral only



K-3069 Neutral only



K-3070 Left or Right



K-3072 Left, Right or Neutral



K-3071 Neutral only

K-3073 Neutral only



K-3074 Left,Right or Neutral



K-3075 Neutral



K-3076 Neutral

WATERTIGHT DOOR BUSHINGS





K-3077 | K-3078 | K-3079 | K-3080 | K-3081 |







LEFTRIGHT

WTD-3401-B WTD-3402-B

Specify I.D., O.D. and length.

K-3082 K-3083



# **PORTLIGHT ACCESSORIES**



PORTLIGHT GLASSES (in all sizes)

K-3047



RETAINING RING WRENCH

K-3048

PORTHOLE GASKETS ALSO AVAILABLE

for porthole glass installation.

#### **BRONZE RETAINING RINGS**

To fit standard portlights.

10"-12"-14"-15"-16"-18"

K-3049

### MISC. BRONZE, BRASS AND STAINLESS STEEL NUTS

**CAP NUTS** 



K-3050



K-3051

**WASHER FACE HEX NUTS** 



K-3052

#### **BUTTERFLY NUTS**



K-3053



SWING NUTS (Bar Nuts)



### MANGANESE BRONZE & ALUMINUM RINGNUTS



K-3056



K-3057



K-3058



K-3059



K-3060



K-3061



K-3062

# WE CAN SUPPLY REPLACEMENT PARTS FOR ALMOST ANY TYPE OF CLOSURE

### WE HAVE IN STOCK OR CAN MANUFACTURE

PACKING PLUNGERS, DOGS, DOG RESTS, SPINDLES HANDWHEELS, BUSHINGS, WASHERS, SPRINGS, GEARS WORMS, HANDLES, TOGGLE BOLTS, WING NUTS, PINS, DEADLIGHTS, SCREENS, REPLACEMENT GLASS

**FOR** 

HATCHES, SCUTTLES, DOORS, PORTLIGHTS

IN

STAINLESS STEEL, NAVAL BRASS, MANGANESE, BRONZE, SILICON BRONZE, STEEL

TO

BUSHIP, CURATOR, HEINTZ

SEND US
MANUFACTURERS' DRAWING NO. AND PART NO.
OR
DRAWING OF PART
OR
THE WORN PART ITSELF
AND
WE CAN REPLACE IT